

Power Distribution Block-Type PDAU

Features

- Snapblock offers a modular design that is easy to assemble
- UL 1953 listed (QPQS) also listed for UL1059 (XCFR2)
- UL assigned short circuit current rating 100k AMP
- Multiple conductor capability
- Dual rated for copper and aluminum conductor
- Range taking design to accommodate cable up to 750 MCM
- Finger safe style

Applications

- Suitable for panel mounting for medium and large sizes and also din rail

Standard Material

- Connector: Aluminum
- Base: Nylon 66

Standard Finish Color


- Gray, Black

Electrical Rating

- Voltage : 600 V
- Temp : 90°C

Certification

- cULus Listed UL1953 (E464522)
- cULus Listed UL1059 (E506183)



Catalog ID	No Of Poles	Amp Rating Per Pole	Conductor Range	Primary No Of Ports/Pole	Wrench Size	Conductor Range	Secondary No Of Ports/Pole	Wrench Size	L	W	H	Size
PDAU-14-2/0-1	1	175	2/0-14		3/16	4-14		Slotted	3.56	1.07	2.56	Small
PDAU-14-2/0-2	2									1.98		
PDAU-14-2/0-3	3									2.88		
PDAU-26-2/0-1	1	350	2/0-14		3/16	4-14		Slotted	5.77	2.03	3.74	Medium
PDAU-26-2/0-2	2									3.85		
PDAU-26-2/0-3	3									5.67		
PDAU-11-2/0-1	1	175	2/0-14		3/16	2/0-14		3/16	3.56	1.07	2.56	Small
PDAU-11-2/0-2	2									1.98		
PDAU-11-2/0-3	3									2.88		
PDAU-22-2/0-1	1	350	2/0-14		3/16	2/0-14		3/16	5.77	2.04	3.74	Medium
PDAU-22-2/0-2	2									3.85		
PDAU-22-2/0-3	3									5.67		
PDAU-212-4/0-1	1	460	4/0-6		4/14	4-14		Slotted	5.77	2.03	3.74	Big
PDAU-212-4/0-2	2									3.85		
PDAU-212-4/0-3	3									5.67		
PDAU-112-250-1	1	255	250-6		3/8	4-14		Slotted	5.77	2.67	3.74	Big
PDAU-112-250-2	2									5.25		
PDAU-112-250-3	3									7.83		
PDAU-112A-250-1	1	255	250-6		3/8	4-14		Slotted	5.77	2.04	3.74	Medium
PDAU-112A-250-2	2									3.85		
PDAU-112A-250-3	3									5.67		
PDAU-212-250-1	1	510	250-6		3/8	4-14		Slotted	5.77	2.67	3.74	Big
PDAU-212-250-2	2									5.25		
PDAU-212-250-3	3									7.83		
PDAU-16-250-1	1	255	250-6		3/8	2/0-14		3/16	5.77	2.67	3.74	Big
PDAU-16-250-2	2									5.25		
PDAU-16-250-3	3									7.83		
PDAU-26-250-1	1	255	250-6		3/8	2/0-14		3/16	5.77	2.67	3.74	Big
PDAU-26-250-2	2									5.25		
PDAU-26-250-3	3									7.83		
PDAU-11-250-1	1	255	250-6		3/8	250-6		3/8	5.77	2.04	3.74	Medium
PDAU-11-250-2	2									3.85		
PDAU-11-250-3	3									5.67		
PDAU-22-250-1	1	510	250-6		3/8	250-6		3/8	5.77	2.67	3.74	Big
PDAU-22-250-2	2									5.25		
PDAU-22-250-3	3									7.83		
PDAU-112-350-1	1	310	350-6		3/8	4-14		Slotted	5.77	2.67	3.74	Big
PDAU-112-350-2	2									5.25		
PDAU-112-350-3	3									7.83		
PDAU-112A-350-1	1	310	350-6		3/8	4-14		Slotted	5.77	2.04	3.74	Medium
PDAU-112A-350-2	2									3.85		
PDAU-112A-350-3	3									5.67		
PDAU-212-350-1	1	620	350-6		3/8	4-14		Slotted	5.77	2.67	3.74	Big
PDAU-212-350-2	2									5.25		
PDAU-212-350-3	3									7.83		

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Mechanical

Power Distribution Blocks



Catalog ID	No OF Poles	Amp Rating Per Pole	Conductor Range	Primary No Of Ports/Pole	Wrench Size	Conductor Range	Secondary No Of Ports/Pole	Wrench Size	L	W	H	Size
PDAU-16-350-1	1	310	350-6		3/8	2/0-14		3/16	5.77	2.67	3.74	Big
PDAU-16-350-2	2									5.25		
PDAU-16-350-3	3									7.83		
PDAU-26-350-1	1	620	350-6		3/8	2/0-14		3/16	5.77	2.67	3.74	Big
PDAU-26-350-2	2									5.25		
PDAU-26-350-3	3									7.83		
PDAU-11-350-1	1	310	350-6		3/8	350-6		3/8	5.77	2.04	3.74	Medium
PDAU-11-350-2	2									3.85		
PDAU-11-350-3	3									5.67		
PDAU-22-350-1	1	620	350-6		3/8	350-6		3/8	5.77	2.67	3.74	Big
PDAU-22-350-2	2									5.25		
PDAU-22-350-3	3									7.83		
PDAU-14-500-1	1	380	500-4		3/8	4/0-14		3/16	5.77	2.67	3.74	Big
PDAU-14-500-2	2									5.25		
PDAU-14-500-3	3									7.83		
PDAU-16-500-1	1	380	500-4		3/8	2/0-14		Slotted	5.77	2.67	3.74	Big
PDAU-16-500-2	2									5.25		
PDAU-16-500-3	3									7.83		
PDAU-112-500-1	1	380	500-4		3/8	4-14		Slotted	5.77	2.67	3.74	Big
PDAU-112-500-2	2									5.25		
PDAU-112-500-3	3									7.83		
PDAU-212-500-1	1	760	500-4		3/8	4-14		Slotted	5.77	2.67	3.74	Big
PDAU-212-500-2	2									5.25		
PDAU-212-500-3	3									7.83		
PDAU-26-500-1	1	760	500-4		3/8	2/0-14		Slotted	5.77	2.67	3.74	Big
PDAU-26-500-2	2									5.25		
PDAU-26-500-3	3									7.83		
PDAU-24-500-1	1	760	500-4		3/8	4/0-6		5/16	5.77	2.67	3.74	Big
PDAU-24-500-2	2									5.25		
PDAU-24-500-3	3									7.83		
PDAU-11-500-1	1	760	500-4		3/8	500-4		3/8	5.77	2.04	3.74	Medium
PDAU-11-500-2	2									3.85		
PDAU-11-500-3	3									5.67		
PDAU-22-500-1	1	760	500-4		3/8	500-4		3/8	5.77	2.67	3.74	Big
PDAU-22-500-2	2									5.25		
PDAU-22-500-3	3									7.83		
PDAU-11-600-1	1	420	600-4		3/8	600-4		3/8	5.77	2.04	3.74	Medium
PDAU-11-600-2	2									3.85		
PDAU-11-600-3	3									5.67		
PDAU-22-600-1	1	840	600-4		3/8	600-4		3/8	5.77	2.67	3.74	Big
PDAU-22-600-2	2									5.25		
PDAU-22-600-3	3									7.83		
PDAU-16-600-1	1	420	600-4		3/8	2/0-14		3/16	5.77	2.67	3.74	Big
PDAU-16-600-2	2									5.25		
PDAU-16-600-3	3									7.83		
PDAU-212-600-1	1	840	600-4		3/8	4-14		Slotted	5.77	2.67	3.74	Big
PDAU-212-600-2	2									5.25		
PDAU-212-600-3	3									7.83		
PDAU-26-600-1	1	840	600-4		3/8	2/0-14		Slotted	5.77	2.67	3.74	Big
PDAU-26-600-2	2									5.25		
PDAU-26-600-3	3									7.83		
PDAU-24-600-1	1	840	600-4		3/8	4/0-6		5/16	5.77	2.67	3.74	Big
PDAU-24-600-2	2									5.25		
PDAU-24-600-3	3									7.83		
PDAU-11-750-1	1	475	750-250		3/8	750-250		3/8	5.77	2.04	3.74	Medium
PDAU-11-750-2	2									3.85		
PDAU-11-750-3	3									5.67		
PDAU-14-750-1	1	475	750-250		3/8	250-6		3/8	5.77	2.67	3.74	Big
PDAU-14-750-2	2									5.25		
PDAU-14-750-3	3									7.83		

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)