

8		7			6			5			4			3			2			1			
Catalog Id		Conductor			Stud Size	Dimensions									Color Code	Installation Tooling				Dieless			
Without Flared Barrel (Fig-1)	With Flared Barrel (Fig-2)	AWG	Flex Conductor G,H,I,K,M & DLO	Expanded Cod. Range		OD	L	B	A	W	T	ØF	E	C		Burndy Model - Y35, Y39, Y750, PAT750, PAT750LI	Ilscos ILC-12-N, ILC-12-H-N, ILCB-12		Huskie Model - EP-510C Die Index				Greeniee HK1240
98046	F98046	#4	-	#4 - #6	1/4	0.34 [8.70]	2.09 [53.00]	0.71 [18.00]	1.26 [32.00]	0.49 [12.40]	0.09 [2.20]	0.25 [6.40]	0.28 [7.10]	0.62 [15.90]	Gray	U4CRT U6CABT	ILD - 4	ILD - 29	HT41AU / HT41GE	KC12-4	Burndy Dieless - PAT444S & PAT4PC834LI. Ilscos Dieless - IDT-6, IDT-6H, IDTB-6, IDTB-6-LIO, TB-6DF1000-P, IDT-12-N, IVTB-6. Greenlee & NSI Dieless - HK12ID, EK12IDL, N12ID.		
98046A	F98046A				1/4	0.34 [8.70]	2.68 [68.00]	0.75 [19.00]	1.81 [46.00]	0.49 [12.40]	0.09 [2.20]	0.25 [6.40]	0.28 [7.10]	1.00 [25.40]									
98046B	F98046B				3/8	0.34 [8.70]	2.68 [68.00]	0.75 [19.00]	1.81 [46.00]	0.57 [14.50]	0.07 [1.70]	0.41 [10.50]	0.38 [9.70]	1.00 [25.40]									
98046C	F98046C				5/16	0.34 [8.70]	2.68 [68.00]	0.75 [19.00]	1.81 [46.00]	0.55 [14.00]	0.09 [2.20]	0.33 [8.40]	0.38 [9.70]	1.00 [25.40]									