


8		7			6			5			4			3			2			1		
Catalog Id		Conductor			Stud Size	Dimensions									Color Code	Installation Tooling				Dieless		
Without Flared Barrel (Fig-1)	With Flared Barrel (Fig-2)	AWG	Flex Conductor G,H,I,K,M & DLO	Expanded Cod. Range		OD	L	B	A	W	T	ØF	E	C		Burndy Model - Y35, Y39, Y750, PAT750, PAT750LI	Ilsco ILC-12-N, ILC-12-H-N, ILCB-12		Huskie Model - EP-510C Die Index		Greeniee HK1240	
98053ANT	F98053ANT				3/8	0.62 [15.80]	3.11 [79.00]	0.98 [25.00]	1.81 [46.00]	0.62 [15.80]	0.12 [3.20]	0.41 [10.50]	0.38 [9.70]	1.00 [25.40]	ORANGE	U27RT	ILD-10	ILD - 50	HT41BA	KC12-3/0	Burndy Dieless - PAT444S & PAT4PC834LI.  Ilsco Dieless -IDT-6, IDT-6H, IDTB-6, IDTB-6-LIO, TB-6DF1000-P,IDT-12-N, IVTB-6.  Greenlee & NSI Dieless - HK12ID, EK12IDL, N12ID.	
98053BNT	F98053BNT				5/16	0.62 [15.80]	3.11 [79.00]	0.98 [25.00]	1.81 [46.00]	0.62 [15.80]	0.12 [3.20]	0.33 [8.40]	0.38 [9.70]	1.00 [25.40]								

Color Code

Typical Stamping


ØF



B

ØOD

T



Note:

- Manufactured from high strength seamless Copper tubing
- Color coded die index and crimp marks
- Electro-Tin plated for corrosion resistance
- Pre-filled with oxide inhibitor and capped with color coded cap.
- UL486A/B Listed for Wire Connectors
- UL Listed and CSA Certified with competitor's compression tools
- Listed for use with class B & C, flex class G, H, I, K, M & DLO cable

**Crimping Instructions**

- Select the proper lug or splice connector for the size of cable being installed, ensuring that the size matches the description in the table.
- Strip the insulation from the cable to a length so that the stripped area of the cable can be completely inserted into and fill the barrel of the lug or splice. Carefully strip the insulation from the cable without nicking the strands.
- Clean the stripped portion of the cable to remove oxide films.
- The stripped portion of the cable must be clean and inserted completely into the connector barrel.
- Using the tool and die combination specified for that connector in the table above, install crimps, leaving a space of 1/8 inch minimum between successive crimps.

For Short Barrel Connectors, apply 1 crimp,  
For Long Barrel Connectors, apply 2 crimps on the color coded bands

Fig 1





Fig 2



TOLERANCE					
OD	L	B	A	W	ØF
±0.20	±1.0	±0.50	±0.50	±1.0	±0.20

TOLERANCES-UNLESS OTHERWISE SPECIFIED		NAME	DATE	<div><div>OEC Usa Inc.</div><div>106 Northfield Avenue, Edison, NJ 08837, Phone: +1 732-479-0469 www.oec-americas.com</div></div>	
2 PL. DEC. ±.015	TRUE C.L. ±.015	DRAWN	R.P.		28.02.25
3 PL. DEC. ±.015	ANGLES ±.015	CHECK	S.P.		28.02.25
		APPROVED	M.K.		28.02.25
DWG. NO. OC-0005	PROJECTION: FIRST ANGLE		SIZE A3	TITLE: Copper Two Hole Standard Barrel Compression Lug Narrow Tang	
MATERIAL Refer Note					
FINISH Refer Note					
				Cat Id. 98053ANT - 98053BNT   REV	
				DO NOT SCALE DRAWING   SHEET 7 OF 17	

THE INFORMATION CONTAINED WITHIN THIS DOCUMENT IS PROPRIETARY TO OEC AND MAY NOT BE DISCLOSED WITHOUT PRIOR WRITTEN CONSENT