

8		7			6		5			4		3			2		1			
Catalog Id		Conductor			Stud Size	Dimensions								Color Code	Installation Tooling				Dieless	
Without Inspection Window (Fig-1)	With Inspection Window (Fig-2)	AWG	Flex Conductor G,H,I,K,M & DLO	Expanded Cod. Range		OD	L	B	A	W	T	ØF	E		Burndy Model - Y35, Y39, Y750, PAT750, PAT750LI	Ilscos ILC-12-N, ILC-12-H-N, ILCB-12		Huskie Model - EP-510C Die Index		Greeniee HK1240
98067	P98067	#2	#3	#2 - #6	5/16	0.42 [10.70]	2.07 [52.60]	1.10 [28.00]	0.81 [20.60]	0.60 [15.30]	0.10 [2.60]	0.34 [8.63]	0.37 [9.40]	Brown	U2CRT	ILD-7	ILD - 33	HT41AW	KC12-2	Burndy Dieless - PAT444S & PAT4PC834LI.  Ilscos Dieless -IDT-6, IDTB-6H, IDTB-6, IDTB-6-LIO, TB-6DF1000-P, IDT-12-N, IVTB-6.  Greenlee & NSI Dieless - HK12ID, EK12IDL, N12ID.
98067A	P98067A				3/8	0.42 [10.70]	2.07 [52.60]	1.10 [28.00]	0.81 [20.60]	0.60 [15.30]	0.10 [2.60]	0.41 [10.41]	0.37 [9.40]							
98067B	P98067B				1/4	0.42 [10.70]	2.07 [52.60]	1.10 [28.00]	0.81 [20.60]	0.60 [15.30]	0.10 [2.60]	0.28 [7.13]	0.37 [9.40]							
98067C	P98067C				#10	0.42 [10.70]	2.07 [52.60]	1.10 [28.00]	0.81 [20.60]	0.60 [15.30]	0.10 [2.60]	0.21 [5.56]	0.37 [9.40]							