

8				7		6		5		4		3		2		1	
CATOLOG ID	Conductor			Stud Size	Dimensions							Color Code	Installation Tooling			Dieless	
	AWG	Flex Conductor G,H,I,K & DLO	Expanded Cod. Range		OD	L	B	W	T	Ø F	E		Burndy Model - Y35, Y39, Y750, PAT750, PAT750LI	Burndy Model - Y35, Y39, Y750, PAT750, PAT750LI With IlSCO	Greeniee HK1240 & EK1240LI		
98502	#6	#6	#6 - #8	1/4	0.33 [8.60]	2.01 [51.00]	0.86 [21.80]	0.57 [14.40]	0.10 [2.50]	0.28 [7.13]	0.38 [9.60]	Gray	U6CABT	ILD-346	KA12-6	Burndy Dieless - PAT444S. Greenlee Dieless - HK12ID & EK12IDL	
98503				5/16	0.33 [8.60]	2.01 [51.00]	0.86 [21.80]	0.57 [14.40]	0.10 [2.50]	0.34 [8.63]	0.38 [9.60]						
98504				3/8	0.33 [8.60]	2.05 [52.00]	0.86 [21.80]	0.65 [16.50]	0.08 [2.00]	0.41 [10.41]	0.38 [9.60]						