CATOLOG ID	Conductor			Stud Size	Dimensions								Color Code	Installation Tooling			Dieless
	AWG	Flex Conductor G,H,I,K,M & DLO	Expanded Cod. Range		OD	L	B	W	T	∅F	E	C		Burndy Model - Y35, Y39, Y750, PAT750, PAT750LI Die Set	Burndy Model - Y35, Y39, Y750, PAT750, PAT750LI with Ilsco Die Set	Greenlee HK1240 & EK1240LI AWG	
98511-2NT	#1	#2	#1 - #6	1/4	0.53 [13.50]	3.43 [87.00]	1.20 [30.50]	0.53 [13.50]	0.24 [6.10]	0.27 [6.80]	0.28 [7.10]	1.00 [25.40]	GOLD	U1CART	ILD-471	KA12-1	Greenlee Dieless - Model HK12ID & EK12IDL Burndy Dieless - Model PAT444
98512-2NT				3/8	0.53 [13.50]	3.53 [89.00]	1.20 [30.50]	0.53 [13.50]	0.24 [6.10]	0.41 [10.50]	0.62 [15.70]	1.00 [25.40]					
98513-2NT				3/8	0.53 [13.50]	4.09 [104.0]	1.20 [30.50]	0.53 [13.50]	0.24 [6.10]	0.41 [10.50]	0.62 [15.70]	1.75 [44.50]					

Note:
- Manufactured from high strength seamless aluminum tubing
- Color coded die index and crimp marks
- Electro-Tin plated for corrosion resistance
- Pre-filled with oxide inhibitor and capped with color coded cap.
- UL486A/B Listed for Wire Connectors
- UL Listed and CSA Certified with competitor's compression tools
- Listed for use with class B & C, flex class G, H, I, K, M & DLO cable









Crimping Instructions

- Select the proper lug or splice connector for the size of cable being installed, ensuring that the size matches the description in the table.
- Strip the insulation from the cable to a length so that the stripped area of the cable can be completely inserted into and fill the barrel of the lug or splice. Carefully strip the insulation from the cable without nicking the strands.
- Clean the stripped portion of the cable to remove oxide films.
- The stripped portion of the cable must be clean and inserted completely into the connector barrel.
- Using the tool and die combination specified for that connector in the table above, install crimps, leaving a space of 1/8 inch minimum between successive crimps.
  For Short Barrel Connectors, apply 1 crimp,
  For Long Barrel Connectors, apply 2 crimps on the color coded bands

TOLERANCE					
OD	L	B	A	W	∅F
±0.20	±1.0	±0.50	±0.50	±1.0	±0.20

TOLERANCES-UNLESS OTHERWISE SPECIFIED
2 PL. DEC. ±.015 TRUE C.L. ±.015
3 PL. DEC. ±.015 ANGLES ±.015

	NAME	DATE
DRAWN	R.P	20.02.25
CHECK	S.P.	20.02.25
APPROVED	M.K.	20.02.25

PROJECTION: FIRST ANGLE

DWG. NO. OC-0023

SIZE A3

MATERIAL Refer Note

FINISH Tin Plated

OEC Usa Inc.
106 Northfield Avenue, Edison, NJ 08837,
Phone: +1 732-479-0469 www.oec-americas.com

TITLE: Aluminum, Two Hole, Long Barrel Compression Lug, Narrow Tang

Cat Id. 98511-2NT-98513-2NT REV

DO NOT SCALE DRAWING SHEET 3 OF 18

THE INFORMATION CONTAINED WITHIN THIS DOCUMENT IS PROPRIETARY TO OEC AND MAY NOT BE DISCLOSED WITHOUT PRIOR WRITTEN CONSENT