

8		7			6			5			4		3			2		1	
Catalog Id		Conductor			Stud Size	Dimensions						Color Code	Installation Tooling				Dieless		
Without Flared Barrel (Fig-1)	With Flared Barrel (Fig-2)	AWG	Flex Conductor G,H,I,K,M & DLO	Expanded Cod. Range		OD	L	B	A	W	T		Burndy Model - Y35, Y39, Y750, PAT750, PAT750LI	IlSCO ILC-12-N, ILC-12-H-N, ILCB-12	Huskie Model - EP-510C Die Index	Greeniee HK1240			
BT98042B	FBT98042B	700	500 (G,H,I,K,M)	700 - 250	5/8	1.24 [31.50]	4.37 [111.00]	1.85 [47.00]	1.85 [47.00]	1.78 [45.20]	0.27 [6.80]	Pink	-	-	-	-	-	Burndy Dieless - PAT444S & PAT4PC834LI. IlSCO Dieless -IDT-6, IDT-6H, IDTB-6, IDTB-6-LIO, TB-6DF1000-P,IDT-12-N, IVTB-6. Greenlee & NSI Dieless - HK12ID, EK12IDL, N12ID.	
BT98042C	FBT98042C		535(DLO)	1/2	1.24 [31.50]	4.37 [111.00]	1.85 [47.00]	1.85 [47.00]	1.78 [45.20]	0.27 [6.80]									