

F

E

D

C

B

A

F

E

D

C

B

A

Catalog Id		Conductor			Stud Size	Dimensions						Color Code	Installation Tooling					Dieless
Without Flared Barrel (Fig-1)	With Flared Barrel (Fig-2)	AWG	Flex Conductor G,H,I,K,M & DLO	Expanded Cod. Range		OD	L	B	A	W	T		Burndy Model - Y35, Y39, Y750, PAT750, PAT750LI	Ilscot ILC-12-N, ILC-12-H-N, ILCB-12		Huskie Model - EP-510C Die Index	Greenlee HK1240	
BT98043B	FBT98043B	1000	750 (G,H,I)	1000 - 750	5/8	1.52 [38.80]	4.43 [112.50]	1.91 [48.50]	1.85 [47.00]	2.18 [55.40]	0.33 [8.40]	White	-	-	-	-	-	Burndy Dieless - PAT444S & PAT4PC834LI. Ilscot Dieless -IDT-6, IDT-6H, IDTB-6, IDTB-6-LIO, TB-6DF1000-P, IDT-12-N, IVTB-6. Greenlee & NSI Dieless - HK12ID, EK12IDL, N12ID.
BT98043C	FBT98043C		777(DLO)		1/2	1.52 [38.80]	4.43 [112.50]	1.91 [48.50]	1.85 [47.00]	2.18 [55.40]	0.33 [8.40]							





Fig-1

Fig-2



- Note:
- Manufactured from high strength seamless Copper tubing
 - Color coded die index and crimp marks
 - Electro-Tin plated for corrosion resistance
 - Pre-filled with oxide inhibitor and capped with color coded cap.
 - UL486A/B Listed for Wire Connectors
 - UL Listed and CSA Certified with competitor's compression tools
 - Listed for use with class B & C, flex class G, H, I, K, M & DLO cable

Crimping Instructions

- Select the proper lug or splice connector for the size of cable being installed, ensuring that the size matches the description in the table.
- Strip the insulation from the cable to a length so that the stripped area of the cable can be completely inserted into and fill the barrel of the lug or splice. Carefully strip the insulation from the cable without nicking the strands.
- Clean the stripped portion of the cable to remove oxide films.
- The stripped portion of the cable must be clean and inserted completely into the connector barrel.
- Using the tool and die combination specified for that connector in the table above, install crimps, leaving a space of 1/8 inch minimum between successive crimps.
For Short Barrel Connectors, apply 1 crimp,
For Long Barrel Connectors, apply 2 crimps on the color coded bands

THE INFORMATION CONTAINED WITHIN THIS DOCUMENT IS PROPRIETARY TO OEC AND MAY NOT BE DISCLOSED WITHOUT PRIOR WRITTEN CONSENT

TOLERANCE				
OD	L	B	A	W
±0.20	±1.0	±0.50	±0.50	±1.0

TOLERANCES-UNLESS OTHERWISE SPECIFIED			NAME	DATE	<div> Usa Inc.</div> <div>106 Northfield Avenue, Edison, NJ 08837, Phone: +1 732-479-0469 www.oec-americas.com</div>	
2 PL. DEC. ±.015 TRUE C.L. ±.015		DRAWN	R.P.	28.02.25		
3 PL. DEC. ±.015 ANGLES ±.015		CHECK	S.P.	28.02.25		
		APPROVED	M.K.	28.02.25		
DWG. NO. OC-0003		PROJECTION:  FIRST ANGLE		SIZE A3	TITLE: Copper One Hole Standard Barrel Compression Lug Blank Tang	
MATERIAL Refer Note						
FINISH Refer Note						
					Cat Id. BT98043B-BT98043C	REV
					DO NOT SCALE DRAWING	SHEET 19 OF 19