

8		7			6		5			4		3		2		1		
Catalog Id		Conductor			Stud Size	Dimensions						Color Code	Installation Tooling				Dieless	
Without Inspection Window (Fig-1)	With Inspection Window (Fig-2)	AWG	Flex Conductor G,H,I,K,M & DLO	Expanded Cod. Range		OD	L	B	A	W	T		Burndy Model - Y35, Y39, Y750, PAT750, PAT750LI	Ilscos ILC-12-N, ILC-12-H-N, ILCB-12	Huskie Model - EP-510C Die Index	Greeniee HK1240		
BT98065	PBT98065	#6	#7	#6 - #8	1/4	0.29 [7.50]	1.77 [45.00]	0.98 [25.00]	0.67 [17.00]	0.42 [10.70]	0.08 [2.10]	Blue	U5CRT U8CABT	ILD - 3	ILD - 24	HT41AT / HT41GL	KC12-6	Burndy Dieless - PAT444S & PAT4PC834LI. Ilscos Dieless - IDT-6, IDT-6H, IDTB-6, IDTB-6-LIO, TB-6DF1000-P, IDT-12-N, IVTB-6. Greenlee & NSI Dieless - HK12ID, EK12IDL, N12ID.
BT98065A	PBT98065A				3/8	0.29 [7.50]	1.91 [48.60]	0.98 [25.00]	0.81 [20.60]	0.59 [15.00]	0.05 [1.30]							
BT98065B	PBT98065B				5/16	0.29 [7.50]	1.91 [48.60]	0.98 [25.00]	0.81 [20.60]	0.51 [13.00]	0.07 [1.80]							
BT98065C	PBT98065C				#10	0.29 [7.50]	1.77 [45.00]	0.98 [25.00]	0.67 [17.00]	0.42 [10.70]	0.08 [2.10]							