

8		7			6	5			4	3		2		1				
Catalog Id		Conductor			Stud Size	Dimensions						Color Code	Installation Tooling				Dieless	
Without Inspection Window (Fig-1)	With Inspection Window (Fig-2)	AWG	Flex Conductor G,H,I,K,M & DLO	Expanded Cod. Range		OD	L	B	A	W	T		Burndy Model - Y35, Y39, Y750, PAT750, PAT750LI	Ilscos ILC-12-N, ILC-12-H-N, ILCB-12	Huskie Model - EP-510C Die Index	Greenlee HK1240		
BT98066D	PBT98066D	#3	#4	#3 - #6	#10	0.37 [9.60]	2.07 [52.60]	1.10 [28.00]	0.81 [20.60]	0.50 [12.70]	0.09 [2.40]	White	U2CRT	-	29	HT41AW	-	Burndy Dieless - PAT444S & PAT4PC834LI. Ilscos Dieless - IDT-6, IDT-6H, IDTB-6, IDTB-6-LIO, TB-6DF1000-P, IDT-12-N, IVTB-6. Greenlee & NSI Dieless - HK12ID, EK12IDL, N12ID.
BT98066E	PBT98066E				1/4	0.37 [9.60]	2.07 [52.60]	1.10 [28.00]	0.81 [20.60]	0.50 [12.70]	0.09 [2.40]							
BT98066F	PBT98066F				5/16	0.37 [9.60]	2.07 [52.60]	1.10 [28.00]	0.81 [20.60]	0.55 [14.00]	0.09 [2.20]							
BT98066G	PBT98066G				3/8	0.37 [9.60]	2.07 [52.60]	1.10 [28.00]	0.81 [20.60]	0.59 [15.00]	0.08 [2.00]							

</