Catalog Id		Conductor			Stud Size	Dimensions						Color Code	Installation Tooling					Dieless
Without Inspection Window (Fig-1)	With Inspection Window (Fig-2)	AWG	Flex Conductor G,H,I,K,M & DLO	Expanded Cod. Range		OD	L	B	A	W	T		Burndy Model - Y35, Y39, Y750, PAT750, PAT750LI	Ilsco ILC-12-N, ILC-12-H-N, ILCB-12		Huskie Model - EP-510C Die Index	Greeniee HK1240	
BT98097	PBT98097	#2/0	#1/0	#2/0 - #4	3/8	0.56 [14.30]	3.42 [87.00]	1.38 [35.00]	1.81 [46.00]	0.81 [20.70]	0.12 [3.00]	Black	U26RT	ILD-10	ILD - 45	HT41AZ	KC12-2/0	Burndy Dieless - PAT444S & PAT4PC834LI. Ilsco Dieless -IDT-6, IDT-6H, IDTB-6, IDTB-6-LIO, TB-6DF1000-P,IDT-12-N, IVTB-6. Greenlee & NSI Dieless - HK12ID, EK12IDL, N12ID.
BT98097A	PBT98097A				1/4	0.56 [14.30]	2.99 [76.00]	1.38 [35.00]	1.38 [35.00]	0.81 [20.70]	0.12 [3.00]							
BT98097B	PBT98097B				1/4	0.56 [14.30]	2.87 [73.00]	1.38 [35.00]	1.26 [32.00]	0.81 [20.70]	0.12 [3.00]							
BT98097C	PBT98097C				1/4	0.56 [14.30]	3.42 [87.00]	1.38 [35.00]	1.81 [46.00]	0.81 [20.70]	0.12 [3.00]							
BT98097D	PBT98097D				3/8	0.56 [14.30]	4.60 [117.00]	1.38 [35.00]	2.99 [76.00]	0.81 [20.70]	0.12 [3.00]							
BT98098	PBT98098				1/2	0.56 [14.30]	4.60 [117.00]	1.38 [35.00]	2.99 [76.00]	0.81 [20.70]	0.12 [3.00]							



Fig-1



Fig-2

Note:
- Manufactured from high strength seamless Copper tubing
- Color coded die index and crimp marks
- Electro-Tin plated for corrosion resistance
- Pre-filled with oxide inhibitor and capped with color coded cap.
- UL486A/B Listed for Wire Connectors
- UL Listed and CSA Certified with competitor's compression tools
- Listed for use with class B & C, flex class G, H, I, K, M & DLO cable

Crimping Instructions

- Select the proper lug or splice connector for the size of cable being installed, ensuring that the size matches the description in the table.
- Strip the insulation from the cable to a length so that the stripped area of the cable can be completely inserted into and fill the barrel of the lug or splice. Carefully strip the insulation from the cable without nicking the strands.
- Clean the stripped portion of the cable to remove oxide films.
- The stripped portion of the cable must be clean and inserted completely into the connector barrel.
- Using the tool and die combination specified for that connector in the table above, install crimps, leaving a space of 1/8 inch minimum between successive crimps.
  For Short Barrel Connectors, apply 1 crimp,
  For Long Barrel Connectors, apply 2 crimps on the color coded bands

TOLERANCE				
OD	L	B	A	W
±0.20	±1.0	±0.50	±0.50	±1.0

TOLERANCES-UNLESS OTHERWISE SPECIFIED		NAME	DATE
2 PL. DEC. ±.015 TRUE C.L. ±.015	DRAWN	R.P	08.03.25
3 PL. DEC. ±.015 ANGLES ±.015	CHECK	S.P.	08.03.25
	APPROVED	M.K.	08.03.25

OEC Usa Inc.
106 Northfield Avenue, Edison, NJ 08837,
Phone: +1 732-479-0469 www.oec-americas.com

DWG. NO. OC-0014
PROJECTION: FIRST ANGLE
SIZE A3
TITLE: Copper Two Hole Long Barrel Compression Lug Blank Tang
MATERIAL Refer Note
FINISH Refer Note
Cat Id. BT98097 - BT98098
REV
DO NOT SCALE DRAWING
SHEET 8 OF 19

THE INFORMATION CONTAINED WITHIN THIS DOCUMENT IS PROPRIETARY TO OEC AND MAY NOT BE DISCLOSED WITHOUT PRIOR WRITTEN CONSENT