

Aluminum, Panelboard Lug, Three Conductor, I-Beam Style Dual Rated (AL9CU)

Features

- Manufactured from high strength aluminum alloy
- Chamfered entry
- Electro-Tin plated for corrosion resistance
- UL486A/B Listed for Wire Connectors
- CSA certified to standard 22.2
- Suitable for use with either copper or aluminum conductors
- Provides low contact resistance
- Saves time and provides ease of installation
- Stacked design

Standard Material

- Aluminum

Standard Finish




- Electro-tin plated

Electrical Rating

- Voltage Rating: 600 V
- Maximum Circuit Rating: 35 kV
- Temperature Rating: 90°C

We Supply

- Suffix "-1/4", "-5/16", "-3/8", "-1/2", "-5/8", for special mounting stud holes.



For Aluminum and Copper Conductors

Catalog ID	Conductor Range	Bolt Size	Dimensions In Inches						Wrench Style		Torque in (lbs)
			L	W	H	T	J	G			
99962	1/0-14	3/8	3.03	1.12	1.41	0.19	1.38	0.44	Allen Hex		120
99963	2/0-14	3/8	3.03	1.24	1.41	0.19	1.38		Allen Hex		120
99964	250-6	3/8	3.81	1.85	2.16	0.27	1.38	0.62	Allen Hex		400
99965	350-6	3/8	3.81	2.00	2.16	0.27	1.38		Allen Hex		275
99966	500-4	3/8	4.92	2.50	2.75	0.35	1.38		Allen Hex		531
99967	600-2	3/8	4.92	2.50	2.75	0.35	1.38		Allen Hex		500
99968	750-1/0	3/8	4.92	2.50	2.99	0.47	1.38		Allen Hex		796

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

We suggest using an oxide inhibitor for every aluminum termination.