

Insulated Multi-Tap Connectors Single Sided Entry

Features

- Insulated with high dielectric access plastisol
- Dual rated for copper and aluminum conductors
- Wire range: 750Kcmil-14
- UL486 A/B Listed for Wire Connectors
- Cold temperature rated up to -45°C
- Pre-filled with oxide inhibitor prevents oxidation moisture and contaminants from entering area
- Supplied with removable access plugs
- Black insulation is UV resistant
- Insulation UV stabilized & listed to UL94 with V0 flammability

Applications

- Suitable for use in panel boards, cable entry, duct and troughs

Standard Material

- Connector- Aluminum
- Screw- Aluminum
- Insulation & Plugs- Plastisol

Standard Finish

- Black/Clear

Certification

- cULus Listed (E208265)
- NEC: 230.46

We Supply

- Suffix 'C' for Clear Product (eg. XXXXXC)



Catalog ID	Catalog ID	Wire Range	No of Port	Dimensions In Inches			Hex Size	Torque in (lbs)
				L	W	H		
60001	60001C	4-14 Sol/Str	02	1.13	1.11	1.38	1/8	35
62001	62001C	4-14 Sol/Str	03	1.69	1.11	1.38	1/8	35
62002	62002C	4-14 Sol/Str	04	2.25	1.11	1.38	1/8	35
62003	62003C	4-14 Sol/Str	05	2.81	1.11	1.38	1/8	35
62004	62004C	4-14 Sol/Str	06	3.37	1.11	1.38	1/8	35
62005	62005C	4-14 Sol/Str	07	3.93	1.11	1.38	1/8	35
62006	62006C	4-14 Sol/Str	08	4.49	1.11	1.38	1/8	35
62007	62007C	4-14 Sol/Str	09	5.05	1.11	1.38	1/8	35
62008	62008C	4-14 Sol/Str	10	5.61	1.11	1.38	1/8	35
62009	62009C	4-14 Sol/Str	11	6.17	1.11	1.38	1/8	35
62010	62010C	4-14 Sol/Str	12	6.73	1.11	1.38	1/8	35
62011	62011C	4-14 Sol/Str	13	7.29	1.11	1.38	1/8	35
62012	62012C	4-14 Sol/Str	14	7.85	1.11	1.38	1/8	35
60003A	60003AC	2-14 Sol/Str	02	1.25	1.20	1.38	Slot Head	100
62013A	62013AC	2-14 Sol/Str	03	1.88	1.20	1.38	Slot Head	100
62014A	62014AC	2-14 Sol/Str	04	2.51	1.20	1.38	Slot Head	100
62015A	62015AC	2-14 Sol/Str	05	3.14	1.20	1.38	Slot Head	100
62016A	62016AC	2-14 Sol/Str	06	3.77	1.20	1.38	Slot Head	100
62017A	62017AC	2-14 Sol/Str	07	4.40	1.20	1.38	Slot Head	100
62018A	62018AC	2-14 Sol/Str	08	5.03	1.20	1.38	Slot Head	100
62019A	62019AC	2-14 Sol/Str	09	5.66	1.20	1.38	Slot Head	100
62020A	62020AC	2-14 Sol/Str	10	6.29	1.20	1.38	Slot Head	100
62021A	62021AC	2-14 Sol/Str	11	6.92	1.20	1.38	Slot Head	100
62022A	62022AC	2-14 Sol/Str	12	7.55	1.20	1.38	Slot Head	100
62023A	62023AC	2-14 Sol/Str	13	8.18	1.20	1.38	Slot Head	100
62024A	62024AC	2-14 Sol/Str	14	8.81	1.20	1.38	Slot Head	100
60003	60003C	1/0-14 Sol/Str	02	1.69	1.39	1.72	3/16	100
62013	62013C	1/0-14 Sol/Str	03	2.54	1.39	1.72	3/16	100
62014	62014C	1/0-14 Sol/Str	04	3.38	1.39	1.72	3/16	100
62015	62015C	1/0-14 Sol/Str	05	4.23	1.39	1.72	3/16	100
62016	62016C	1/0-14 Sol/Str	06	5.07	1.39	1.72	3/16	100
62017	62017C	1/0-14 Sol/Str	07	5.92	1.39	1.72	3/16	100
62018	62018C	1/0-14 Sol/Str	08	6.76	1.39	1.72	3/16	100
62019	62019C	1/0-14 Sol/Str	09	7.61	1.39	1.72	3/16	100
62020	62020C	1/0-14 Sol/Str	10	8.45	1.39	1.72	3/16	100
62021	62021C	1/0-14 Sol/Str	11	9.30	1.39	1.72	3/16	100
62022	62022C	1/0-14 Sol/Str	12	10.14	1.39	1.72	3/16	100
62023	62023C	1/0-14 Sol/Str	13	10.99	1.39	1.72	3/16	100
62024	62024C	1/0-14 Sol/Str	14	11.83	1.39	1.72	3/16	100

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)



Insulated Multi-Tap Connectors Single Sided Entry

Catalog ID	Catalog ID	Wire Range	No of Port	Dimensions In Inches			Hex Size	Torque in (lbs)
				L	W	H		
60005A	60005AC	2/0-14 Sol/Str	02	1.69	1.53	1.72	3/16	100
62025A	62025AC	2/0-14 Sol/Str	03	2.54	1.53	1.72	3/16	100
62026A	62026AC	2/0-14 Sol/Str	04	3.38	1.53	1.72	3/16	100
62027A	62027AC	2/0-14 Sol/Str	05	4.23	1.53	1.72	3/16	100
62028A	62028AC	2/0-14 Sol/Str	06	5.07	1.53	1.72	3/16	100
62029A	62029AC	2/0-14 Sol/Str	07	5.92	1.53	1.72	3/16	100
62030A	62030AC	2/0-14 Sol/Str	08	6.76	1.53	1.72	3/16	100
62031A	62031AC	2/0-14 Sol/Str	09	7.61	1.53	1.72	3/16	100
62032A	62032AC	2/0-14 Sol/Str	10	8.45	1.53	1.72	3/16	100
62033A	62033AC	2/0-14 Sol/Str	11	9.30	1.53	1.72	3/16	100
62034A	62034AC	2/0-14 Sol/Str	12	10.14	1.53	1.72	3/16	100
62035A	62035AC	2/0-14 Sol/Str	13	10.99	1.53	1.72	3/16	100
62036A	62036AC	2/0-14 Sol/Str	14	11.83	1.53	1.72	3/16	100
60005	60005C	3/0-14 Sol/Str	02	2.00	1.70	2.00	1/4	100
62025	62025C	3/0-14 Sol/Str	03	3.00	1.70	2.00	1/4	100
62026	62026C	3/0-14 Sol/Str	04	4.00	1.70	2.00	1/4	100
62027	62027C	3/0-14 Sol/Str	05	5.00	1.70	2.00	1/4	100
62028	62028C	3/0-14 Sol/Str	06	6.00	1.70	2.00	1/4	100
62029	62029C	3/0-14 Sol/Str	07	7.00	1.70	2.00	1/4	100
62030	62030C	3/0-14 Sol/Str	08	8.00	1.70	2.00	1/4	100
62031	62031C	3/0-14 Sol/Str	09	9.00	1.70	2.00	1/4	100
62032	62032C	3/0-14 Sol/Str	10	10.00	1.70	2.00	1/4	100
62033	62033C	3/0-14 Sol/Str	11	11.00	1.70	2.00	1/4	100
62034	62034C	3/0-14 Sol/Str	12	12.00	1.70	2.00	1/4	100
62035	62035C	3/0-14 Sol/Str	13	13.00	1.70	2.00	1/4	100
62036	62036C	3/0-14 Sol/Str	14	14.00	1.70	2.00	1/4	100
60006A	60006AC	250 Kcmil-10 Sol/Str	02	2.18	2.04	2.20	5/16	150
62037	62037C	250 Kcmil-10 Sol/Str	03	3.27	2.04	2.20	5/16	150
62038	62038C	250 Kcmil-10 Sol/Str	04	4.36	2.04	2.20	5/16	150
62039	62039C	250 Kcmil-10 Sol/Str	05	5.45	2.04	2.20	5/16	150
62040	62040C	250 Kcmil-10 Sol/Str	06	6.54	2.04	2.20	5/16	150
62041	62041C	250 Kcmil-10 Sol/Str	07	7.63	2.04	2.20	5/16	150
62042	62042C	250 Kcmil-10 Sol/Str	08	8.72	2.04	2.20	5/16	150
62043	62043C	250 Kcmil-10 Sol/Str	09	9.81	2.04	2.20	5/16	150
62044	62044C	250 Kcmil-10 Sol/Str	10	10.90	2.04	2.20	5/16	150
62045	62045C	250 Kcmil-10 Sol/Str	11	11.99	2.04	2.20	5/16	150
62046	62046C	250 Kcmil-10 Sol/Str	12	13.08	2.04	2.20	5/16	150
62047	62047C	250 Kcmil-10 Sol/Str	13	14.17	2.04	2.20	5/16	150
62048	62048C	250 Kcmil-10 Sol/Str	14	15.26	2.04	2.20	5/16	150
60007A	60007AC	350 Kcmil-10 Sol/Str	02	2.37	2.34	2.40	5/16	225
62049	62049C	350 Kcmil-10 Sol/Str	03	3.56	2.34	2.40	5/16	225
62050	62050C	350 Kcmil-10 Sol/Str	04	4.74	2.34	2.40	5/16	225
62051	62051C	350 Kcmil-10 Sol/Str	05	5.93	2.34	2.40	5/16	225
62052	62052C	350 Kcmil-10 Sol/Str	06	7.11	2.34	2.40	5/16	225
62053	62053C	350 Kcmil-10 Sol/Str	07	8.30	2.34	2.40	5/16	225
62054	62054C	350 Kcmil-10 Sol/Str	08	9.48	2.34	2.40	5/16	225
62055	62055C	350 Kcmil-10 Sol/Str	09	10.67	2.34	2.40	5/16	225
62056	62056C	350 Kcmil-10 Sol/Str	10	11.85	2.34	2.40	5/16	225
62057	62057C	350 Kcmil-10 Sol/Str	11	13.04	2.34	2.40	5/16	225
62058	62058C	350 Kcmil-10 Sol/Str	12	14.22	2.34	2.40	5/16	225
62059	62059C	350 Kcmil-10 Sol/Str	13	15.41	2.34	2.40	5/16	225
62060	62060C	350 Kcmil-10 Sol/Str	14	16.59	2.34	2.40	5/16	225

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Insulated Multi-Tap Connectors Single Sided Entry

Catalog ID	Catalog ID	Wire Range	No of Port	Dimensions In Inches			Hex Size	Torque in (lbs)
				L	W	H		
60008A	60008AC	500 Kcmil-6 Str	02	2.80	2.55	2.90	5/16	310
62061	62061C	500 Kcmil-6 Str	03	4.20	2.55	2.90	5/16	310
62062	62062C	500 Kcmil-6 Str	04	5.60	2.55	2.90	5/16	310
62063	62063C	500 Kcmil-6 Str	05	7.00	2.55	2.90	5/16	310
62064	62064C	500 Kcmil-6 Str	06	8.40	2.55	2.90	5/16	310
62065	62065C	500 Kcmil-6 Str	07	9.80	2.55	2.90	5/16	310
62066	62066C	500 Kcmil-6 Str	08	11.20	2.55	2.90	5/16	310
62067	62067C	500 Kcmil-6 Str	09	12.60	2.55	2.90	5/16	310
62068	62068C	500 Kcmil-6 Str	10	14.00	2.55	2.90	5/16	310
62069	62069C	500 Kcmil-6 Str	11	15.40	2.55	2.90	5/16	310
62070	62070C	500 Kcmil-6 Str	12	16.80	2.55	2.90	5/16	310
62071	62071C	500 Kcmil-6 Str	13	18.20	2.55	2.90	5/16	310
62072	62072C	500 Kcmil-6 Str	14	19.60	2.55	2.90	5/16	310
60009B	60009BC	600 Kcmil-6 Str	02	2.80	2.55	2.90	5/16	442
62073A	62073AC	600 Kcmil-6 Str	03	4.20	2.55	2.90	5/16	442
62074A	62074AC	600 Kcmil-6 Str	04	5.60	2.55	2.90	5/16	442
62075A	62075AC	600 Kcmil-6 Str	05	7.00	2.55	2.90	5/16	442
62076A	62076AC	600 Kcmil-6 Str	06	8.40	2.55	2.90	5/16	442
62077A	62077AC	600 Kcmil-6 Str	07	9.80	2.55	2.90	5/16	442
62078A	62078AC	600 Kcmil-6 Str	08	11.20	2.55	2.90	5/16	442
62079A	62079AC	600 Kcmil-6 Str	09	12.60	2.55	2.90	5/16	442
62080A	62080AC	600 Kcmil-6 Str	10	14.00	2.55	2.90	5/16	442
62081A	62081AC	600 Kcmil-6 Str	11	15.40	2.55	2.90	5/16	442
62082A	62082AC	600 Kcmil-6 Str	12	16.80	2.55	2.90	5/16	442
62083A	62083AC	600 Kcmil-6 Str	13	18.20	2.55	2.90	5/16	442
62084A	62084AC	600 Kcmil-6 Str	14	19.60	2.55	2.90	5/16	442
60010A	60010AC	750 Kcmil-2 Str	02	5.00	3.08	3.20	3/8	442
62073	62073C	750 Kcmil-2 Str	03	7.50	3.08	3.20	3/8	442
62074	62074C	750 Kcmil-2 Str	04	10.00	3.08	3.20	3/8	442
62075	62075C	750 Kcmil-2 Str	05	12.50	3.08	3.20	3/8	442
62076	62076C	750 Kcmil-2 Str	06	15.00	3.08	3.20	3/8	442
62077	62077C	750 Kcmil-2 Str	07	17.50	3.08	3.20	3/8	442
62078	62078C	750 Kcmil-2 Str	08	20.00	3.08	3.20	3/8	442
62079	62079C	750 Kcmil-2 Str	09	22.50	3.08	3.20	3/8	442
62080	62080C	750 Kcmil-2 Str	10	25.00	3.08	3.20	3/8	442
62081	62081C	750 Kcmil-2 Str	11	27.50	3.08	3.20	3/8	442
62082	62082C	750 Kcmil-2 Str	12	30.00	3.08	3.20	3/8	442
62083	62083C	750 Kcmil-2 Str	13	32.50	3.08	3.20	3/8	442
62084	62084C	750 Kcmil-2 Str	14	35.00	3.08	3.20	3/8	442

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)