

Insulated Multi-Tap Connectors Dual Sided Entry

Features

- Insulated with high dielectric access plastisol
- Dual rated for copper and aluminum conductors
- Wire range: 750Kcmil-14
- UL486 A/B Listed for Wire Connectors
- Cold temperature rated up to -45°C
- Pre-filled with oxide inhibitor prevents oxidation moisture and contaminants from entering area
- Supplied with removable access plugs
- Black insulation is UV resistant
- Insulation UV stabilized & listed to UL94 with V0 flammability

Applications

- Suitable for use in panel boards, cable entry, duct and troughs

Standard Finish

- Black/Clear

Standard Material

- Connector- Aluminum
- Screw- Aluminum
- Insulation & Plugs- Plastisol

Certification

- cULus Listed (E208265)
- NEC: 230.46

We Supply

- Suffix 'C' for Clear Product (eg. XXXXXC)



Catalog ID	Catalog ID	Wire Range	No of Port	Dimensions In Inches			Hex Size	Torque in (lbs)
				L	W	H		
60002	60002C	4-14 Sol/Str	02	1.13	1.31	1.38	1/8	35
63001A	63001AC	4-14 Sol/Str	03	1.69	1.31	1.38	1/8	35
63002A	63002AC	4-14 Sol/Str	04	2.25	1.31	1.38	1/8	35
63003A	63003AC	4-14 Sol/Str	05	2.81	1.31	1.38	1/8	35
63004A	63004AC	4-14 Sol/Str	06	3.37	1.31	1.38	1/8	35
63005A	63005AC	4-14 Sol/Str	07	3.93	1.31	1.38	1/8	35
63006A	63006AC	4-14 Sol/Str	08	4.49	1.31	1.38	1/8	35
63007A	63007AC	4-14 Sol/Str	09	5.05	1.31	1.38	1/8	35
63008A	63008AC	4-14 Sol/Str	10	5.61	1.31	1.38	1/8	35
63009A	63009AC	4-14 Sol/Str	11	6.17	1.31	1.38	1/8	35
63010A	63010AC	4-14 Sol/Str	12	6.73	1.31	1.38	1/8	35
60003B	60003BC	2-14 Sol/Str	02	1.25	1.41	1.38	Slot Head	100
63013B	63013BC	2-14 Sol/Str	03	1.88	1.41	1.38	Slot Head	100
63014B	63014BC	2-14 Sol/Str	04	2.51	1.41	1.38	Slot Head	100
63015B	63015BC	2-14 Sol/Str	05	3.14	1.41	1.38	Slot Head	100
63016B	63016BC	2-14 Sol/Str	06	3.77	1.41	1.38	Slot Head	100
63017B	63017BC	2-14 Sol/Str	07	4.40	1.41	1.38	Slot Head	100
63018B	63018BC	2-14 Sol/Str	08	5.03	1.41	1.38	Slot Head	100
63019B	63019BC	2-14 Sol/Str	09	5.66	1.41	1.38	Slot Head	100
63020B	63020BC	2-14 Sol/Str	10	6.29	1.41	1.38	Slot Head	100
63021B	63021BC	2-14 Sol/Str	11	6.92	1.41	1.38	Slot Head	100
63022B	63022BC	2-14 Sol/Str	12	7.55	1.41	1.38	Slot Head	100
60003D	60003DC	1/0-14 Sol/Str	02	1.69	1.64	1.72	3/16	100
60004A	60004AC	2/0-14 Sol/Str	02	1.69	1.80	1.72	3/16	100
63001B	63001BC	2/0-14 Sol/Str	03	2.54	1.80	1.72	3/16	100
63002B	63002BC	2/0-14 Sol/Str	04	3.38	1.80	1.72	3/16	100
63003B	63003BC	2/0-14 Sol/Str	05	4.23	1.80	1.72	3/16	100
63004B	63004BC	2/0-14 Sol/Str	06	5.07	1.80	1.72	3/16	100
63005B	63005BC	2/0-14 Sol/Str	07	5.92	1.80	1.72	3/16	100
63006B	63006BC	2/0-14 Sol/Str	08	6.76	1.80	1.72	3/16	100
63007B	63007BC	2/0-14 Sol/Str	09	7.61	1.80	1.72	3/16	100
63008B	63008BC	2/0-14 Sol/Str	10	8.45	1.80	1.72	3/16	100
63009B	63009BC	2/0-14 Sol/Str	11	9.30	1.80	1.72	3/16	100
63010B	63010BC	2/0-14 Sol/Str	12	10.14	1.80	1.72	3/16	100
60004	60004C	3/0-14 Sol/Str	02	2.00	2.00	2.00	1/4	100
63001	63001C	3/0-14 Sol/Str	03	3.00	2.00	2.00	1/4	100
63002	63002C	3/0-14 Sol/Str	04	4.00	2.00	2.00	1/4	100
63003	63003C	3/0-14 Sol/Str	05	5.00	2.00	2.00	1/4	100
63004	63004C	3/0-14 Sol/Str	06	6.00	2.00	2.00	1/4	100
63005	63005C	3/0-14 Sol/Str	07	7.00	2.00	2.00	1/4	100
63006	63006C	3/0-14 Sol/Str	08	8.00	2.00	2.00	1/4	100
63007	63007C	3/0-14 Sol/Str	09	9.00	2.00	2.00	1/4	100
63008	63008C	3/0-14 Sol/Str	10	10.00	2.00	2.00	1/4	100
63009	63009C	3/0-14 Sol/Str	11	11.00	2.00	2.00	1/4	100
63010	63010C	3/0-14 Sol/Str	12	12.00	2.00	2.00	1/4	100

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Insulated Multi-Tap Connectors

Dual Sided Entry

Catalog ID	Catalog ID	Wire Range	No of Port	Dimensions In Inches			Hex Size	Torque in (lbs)
				L	W	H		
60006	60006C	250 Kcmil-10 Sol/Str	02	2.18	2.40	2.20	5/16	150
63011	63011C	250 Kcmil-10 Sol/Str	03	3.27	2.40	2.20	5/16	150
63012	63012C	250 Kcmil-10 Sol/Str	04	4.36	2.40	2.20	5/16	150
63013	63013C	250 Kcmil-10 Sol/Str	05	5.45	2.40	2.20	5/16	150
63014	63014C	250 Kcmil-10 Sol/Str	06	6.54	2.40	2.20	5/16	150
63015	63015C	250 Kcmil-10 Sol/Str	07	7.63	2.40	2.20	5/16	150
63016	63016C	250 Kcmil-10 Sol/Str	08	8.72	2.40	2.20	5/16	150
63017	63017C	250 Kcmil-10 Sol/Str	09	9.81	2.40	2.20	5/16	150
63018	63018C	250 Kcmil-10 Sol/Str	10	10.90	2.40	2.20	5/16	150
63019	63019C	250 Kcmil-10 Sol/Str	11	11.99	2.40	2.20	5/16	150
63020	63020C	250 Kcmil-10 Sol/Str	12	13.08	2.40	2.20	5/16	150
60007	60007C	350 Kcmil-10 Sol/Str	02	2.37	2.75	2.40	5/16	225
63021	63021C	350 Kcmil-10 Sol/Str	03	3.56	2.75	2.40	5/16	225
63022	63022C	350 Kcmil-10 Sol/Str	04	4.74	2.75	2.40	5/16	225
63023	63023C	350 Kcmil-10 Sol/Str	05	5.93	2.75	2.40	5/16	225
63024	63024C	350 Kcmil-10 Sol/Str	06	7.11	2.75	2.40	5/16	225
63025	63025C	350 Kcmil-10 Sol/Str	07	8.30	2.75	2.40	5/16	225
63026	63026C	350 Kcmil-10 Sol/Str	08	9.48	2.75	2.40	5/16	225
63027	63027C	350 Kcmil-10 Sol/Str	09	10.67	2.75	2.40	5/16	225
63028	63028C	350 Kcmil-10 Sol/Str	10	11.85	2.75	2.40	5/16	225
63029	63029C	350 Kcmil-10 Sol/Str	11	13.04	2.75	2.40	5/16	225
63030	63030C	350 Kcmil-10 Sol/Str	12	14.22	2.75	2.40	5/16	225
60008	60008C	500 Kcmil-6 Str	02	2.80	3.00	2.90	5/16	310
63031	63031C	500 Kcmil-6 Str	03	4.20	3.00	2.90	5/16	310
63032	63032C	500 Kcmil-6 Str	04	5.60	3.00	2.90	5/16	310
63033	63033C	500 Kcmil-6 Str	05	7.00	3.00	2.90	5/16	310
63034	63034C	500 Kcmil-6 Str	06	8.40	3.00	2.90	5/16	310
63035	63035C	500 Kcmil-6 Str	07	9.80	3.00	2.90	5/16	310
63036	63036C	500 Kcmil-6 Str	08	11.20	3.00	2.90	5/16	310
63037	63037C	500 Kcmil-6 Str	09	12.60	3.00	2.90	5/16	310
63038	63038C	500 Kcmil-6 Str	10	14.00	3.00	2.90	5/16	310
63039	63039C	500 Kcmil-6 Str	11	15.40	3.00	2.90	5/16	310
63040	63040C	500 Kcmil-6 Str	12	16.80	3.00	2.90	5/16	310
60009A	60009AC	600 Kcmil-6 Str	02	2.80	3.00	2.90	5/16	442
63041B	63041BC	600 Kcmil-6 Str	03	4.20	3.00	2.90	5/16	442
63042B	63042BC	600 Kcmil-6 Str	04	5.60	3.00	2.90	5/16	442
63043B	63043BC	600 Kcmil-6 Str	05	7.00	3.00	2.90	5/16	442
63044B	63044BC	600 Kcmil-6 Str	06	8.40	3.00	2.90	5/16	442
63045B	63045BC	600 Kcmil-6 Str	07	9.80	3.00	2.90	5/16	442
63046B	63046BC	600 Kcmil-6 Str	08	11.20	3.00	2.90	5/16	442
63047B	63047BC	600 Kcmil-6 Str	09	12.60	3.00	2.90	5/16	442
63048B	63048BC	600 Kcmil-6 Str	10	14.00	3.00	2.90	5/16	442
63049B	63049BC	600 Kcmil-6 Str	11	15.40	3.00	2.90	5/16	442
63050B	63050BC	600 Kcmil-6 Str	12	16.80	3.00	2.90	5/16	442
60010	60010C	750 Kcmil-2 Str	02	5.00	3.62	3.20	3/8	442
63041	63041C	750 Kcmil-2 Str	03	7.50	3.62	3.20	3/8	442
63042	63042C	750 Kcmil-2 Str	04	10.00	3.62	3.20	3/8	442
63043	63043C	750 Kcmil-2 Str	05	12.50	3.62	3.20	3/8	442
63044	63044C	750 Kcmil-2 Str	06	15.00	3.62	3.20	3/8	442
63045	63045C	750 Kcmil-2 Str	07	17.50	3.62	3.20	3/8	442
63046	63046C	750 Kcmil-2 Str	08	20.00	3.62	3.20	3/8	442
63047	63047C	750 Kcmil-2 Str	09	22.50	3.62	3.20	3/8	442
63048	63048C	750 Kcmil-2 Str	10	25.00	3.62	3.20	3/8	442
63049	63049C	750 Kcmil-2 Str	11	27.50	3.62	3.20	3/8	442
63050	63050C	750 Kcmil-2 Str	12	30.00	3.62	3.20	3/8	442

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)