

Insulated Multi-Tap Connectors Dual Sided Entry with Mounting

Features

- Insulated with high dielectric access plastisol
- Dual rated for copper and aluminum conductors
- Wire range: 750Kcmil-14
- UL486 A/B Listed for Wire Connectors
- Cold temperature rated up to -45°C
- Pre-filled with oxide inhibitor prevents oxidation moisture and contaminants from entering area
- Supplied with removable access plugs
- Black insulation is UV resistant
- Insulation UV stabilized & listed to UL94 with V0 flammability

Applications

- Suitable for use in panel boards, cable entry, duct and troughs

Standard Material

- Connector- Aluminum
- Screw- Aluminum
- Insulation & Plugs- Plastisol

Standard Finish


- Black/Clear

Certification

- cULus Listed (E208265)
- NEC: 230.46

We Supply

- Suffix 'C' for Clear Product (eg. XXXXXC)



LISTED
WIRE
CONNECTOR
11MB

Catalog ID	Catalog ID	Wire Range	No of Port	Dimensions In Inches			Hex Size	Torque in (lbs)
				L	W	H		
60002M	60002MC	4-14 Sol/Str	02	2.26	1.31	1.38	1/8	35
65001A	65001AC	4-14 Sol/Str	03	2.81	1.31	1.38	1/8	35
65002A	65002AC	4-14 Sol/Str	04	3.37	1.31	1.38	1/8	35
65003A	65003AC	4-14 Sol/Str	05	3.93	1.31	1.38	1/8	35
65004A	65004AC	4-14 Sol/Str	06	4.49	1.31	1.38	1/8	35
65005A	65005AC	4-14 Sol/Str	07	5.05	1.31	1.38	1/8	35
65006A	65006AC	4-14 Sol/Str	08	5.61	1.31	1.38	1/8	35
65007A	65007AC	4-14 Sol/Str	09	6.17	1.31	1.38	1/8	35
65008A	65008AC	4-14 Sol/Str	10	6.73	1.31	1.38	1/8	35
65009A	65009AC	4-14 Sol/Str	11	7.29	1.31	1.38	1/8	35
65010A	65010AC	4-14 Sol/Str	12	7.85	1.31	1.38	1/8	35
60003BM	60003BMC	2-14 Sol/Str	02	2.5	1.41	1.38	Slot Head	100
65013B	65013BC	2-14 Sol/Str	03	3.14	1.41	1.38	Slot Head	100
65014B	65014BC	2-14 Sol/Str	04	3.77	1.41	1.38	Slot Head	100
65015B	65015BC	2-14 Sol/Str	05	4.40	1.41	1.38	Slot Head	100
65016B	65016BC	2-14 Sol/Str	06	5.03	1.41	1.38	Slot Head	100
65017B	65017BC	2-14 Sol/Str	07	5.66	1.41	1.38	Slot Head	100
65018B	65018BC	2-14 Sol/Str	08	6.29	1.41	1.38	Slot Head	100
65019B	65019BC	2-14 Sol/Str	09	6.92	1.41	1.38	Slot Head	100
65020B	65020BC	2-14 Sol/Str	10	7.55	1.41	1.38	Slot Head	100
65021B	65021BC	2-14 Sol/Str	11	8.18	1.41	1.38	Slot Head	100
65022B	65022BC	2-14 Sol/Str	12	8.81	1.41	1.38	Slot Head	100
60003DM	60003DMC	1/0-14 Sol/Str	02	3.38	1.64	1.72	3/16	100
60004AM	60004AMC	2/0-14 Sol/Str	02	3.38	1.80	1.72	3/16	100
65001B	65001BC	2/0-14 Sol/Str	03	4.23	1.80	1.72	3/16	100
65002B	65002BC	2/0-14 Sol/Str	04	5.07	1.80	1.72	3/16	100
65003B	65003BC	2/0-14 Sol/Str	05	5.92	1.80	1.72	3/16	100
65004B	65004BC	2/0-14 Sol/Str	06	6.76	1.80	1.72	3/16	100
65005B	65005BC	2/0-14 Sol/Str	07	7.61	1.80	1.72	3/16	100
65006B	65006BC	2/0-14 Sol/Str	08	8.45	1.80	1.72	3/16	100
65007B	65007BC	2/0-14 Sol/Str	09	9.30	1.80	1.72	3/16	100
65008B	65008BC	2/0-14 Sol/Str	10	10.14	1.80	1.72	3/16	100
65009B	65009BC	2/0-14 Sol/Str	11	10.99	1.80	1.72	3/16	100
65010B	65010BC	2/0-14 Sol/Str	12	11.83	1.80	1.72	3/16	100
60004M	60004MC	3/0-14 Sol/Str	02	4.00	2.00	2.00	1/4	100
65001	65001C	3/0-14 Sol/Str	03	5.00	2.00	2.00	1/4	100
65002	65002C	3/0-14 Sol/Str	04	6.00	2.00	2.00	1/4	100
65003	65003C	3/0-14 Sol/Str	05	7.00	2.00	2.00	1/4	100
65004	65004C	3/0-14 Sol/Str	06	8.00	2.00	2.00	1/4	100
65005	65005C	3/0-14 Sol/Str	07	9.00	2.00	2.00	1/4	100
65006	65006C	3/0-14 Sol/Str	08	10.00	2.00	2.00	1/4	100
65007	65007C	3/0-14 Sol/Str	09	11.00	2.00	2.00	1/4	100
65008	65008C	3/0-14 Sol/Str	10	12.00	2.00	2.00	1/4	100
65009	65009C	3/0-14 Sol/Str	11	13.00	2.00	2.00	1/4	100
65010	65010C	3/0-14 Sol/Str	12	14.00	2.00	2.00	1/4	100

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)



Insulated Multi-Tap Connectors Dual Sided Entry with Mounting

Catalog ID	Catalog ID	Wire Range	No of Port	Dimensions In Inches			Hex Size	Torque in (lbs)
				L	W	H		
60006M	60006MC	250 Kcmil-10 Sol/Str	02	4.36	2.40	2.20	5/16	150
65011	65011C	250 Kcmil-10 Sol/Str	03	5.45	2.40	2.20	5/16	150
65012	65012C	250 Kcmil-10 Sol/Str	04	6.54	2.40	2.20	5/16	150
65013	65013C	250 Kcmil-10 Sol/Str	05	7.63	2.40	2.20	5/16	150
65014	65014C	250 Kcmil-10 Sol/Str	06	8.72	2.40	2.20	5/16	150
65015	65015C	250 Kcmil-10 Sol/Str	07	9.81	2.40	2.20	5/16	150
65016	65016C	250 Kcmil-10 Sol/Str	08	10.90	2.40	2.20	5/16	150
65017	65017C	250 Kcmil-10 Sol/Str	09	11.99	2.40	2.20	5/16	150
65018	65018C	250 Kcmil-10 Sol/Str	10	13.08	2.40	2.20	5/16	150
65019	65019C	250 Kcmil-10 Sol/Str	11	14.17	2.40	2.20	5/16	150
65020	65020C	250 Kcmil-10 Sol/Str	12	15.26	2.40	2.20	5/16	150
60007M	60007MC	350 Kcmil-10 Sol/Str	02	4.74	2.75	2.40	5/16	225
65021	65021C	350 Kcmil-10 Sol/Str	03	5.93	2.75	2.40	5/16	225
65022	65022C	350 Kcmil-10 Sol/Str	04	7.11	2.75	2.40	5/16	225
65023	65023C	350 Kcmil-10 Sol/Str	05	8.30	2.75	2.40	5/16	225
65024	65024C	350 Kcmil-10 Sol/Str	06	9.48	2.75	2.40	5/16	225
65025	65025C	350 Kcmil-10 Sol/Str	07	10.67	2.75	2.40	5/16	225
65026	65026C	350 Kcmil-10 Sol/Str	08	11.85	2.75	2.40	5/16	225
65027	65027C	350 Kcmil-10 Sol/Str	09	13.04	2.75	2.40	5/16	225
65028	65028C	350 Kcmil-10 Sol/Str	10	14.22	2.75	2.40	5/16	225
65029	65029C	350 Kcmil-10 Sol/Str	11	15.41	2.75	2.40	5/16	225
65030	65030C	350 Kcmil-10 Sol/Str	12	16.59	2.75	2.40	5/16	225
60008AM	60008AMC	500 Kcmil-6 Str	02	5.60	3.00	2.90	5/16	310
65031	65031C	500 Kcmil-6 Str	03	7.00	3.00	2.90	5/16	310
65032	65032C	500 Kcmil-6 Str	04	8.40	3.00	2.90	5/16	310
65033	65033C	500 Kcmil-6 Str	05	9.80	3.00	2.90	5/16	310
65034	65034C	500 Kcmil-6 Str	06	11.20	3.00	2.90	5/16	310
65035	65035C	500 Kcmil-6 Str	07	12.60	3.00	2.90	5/16	310
65036	65036C	500 Kcmil-6 Str	08	14.00	3.00	2.90	5/16	310
65037	65037C	500 Kcmil-6 Str	09	15.40	3.00	2.90	5/16	310
65038	65038C	500 Kcmil-6 Str	10	16.80	3.00	2.90	5/16	310
65039	65039C	500 Kcmil-6 Str	11	18.20	3.00	2.90	5/16	310
65040	65040C	500 Kcmil-6 Str	12	19.60	3.00	2.90	5/16	310
60009BM	60009BMC	600 Kcmil-6 Str	02	5.60	3.00	2.90	5/16	442
65041B	65041BC	600 Kcmil-6 Str	03	7.00	3.00	2.90	5/16	442
65042B	65042BC	600 Kcmil-6 Str	04	8.40	3.00	2.90	5/16	442
65043B	65043BC	600 Kcmil-6 Str	05	9.80	3.00	2.90	5/16	442
65044B	65044BC	600 Kcmil-6 Str	06	11.20	3.00	2.90	5/16	442
65045B	65045BC	600 Kcmil-6 Str	07	12.60	3.00	2.90	5/16	442
65046B	65046BC	600 Kcmil-6 Str	08	14.00	3.00	2.90	5/16	442
65047B	65047BC	600 Kcmil-6 Str	09	15.40	3.00	2.90	5/16	442
65048B	65048BC	600 Kcmil-6 Str	10	16.80	3.00	2.90	5/16	442
65049B	65049BC	600 Kcmil-6 Str	11	18.20	3.00	2.90	5/16	442
65050B	65050BC	600 Kcmil-6 Str	12	19.60	3.00	2.90	5/16	442
60010M	60010MC	750 Kcmil-2 Str	02	10.00	3.62	3.20	3/8	442
65041	65041C	750 Kcmil-2 Str	03	12.50	3.62	3.20	3/8	442
65042	65042C	750 Kcmil-2 Str	04	15.00	3.62	3.20	3/8	442
65043	65043C	750 Kcmil-2 Str	05	17.50	3.62	3.20	3/8	442
65044	65044C	750 Kcmil-2 Str	06	20.00	3.62	3.20	3/8	442
65045	65045C	750 Kcmil-2 Str	07	22.50	3.62	3.20	3/8	442
65046	65046C	750 Kcmil-2 Str	08	25.00	3.62	3.20	3/8	442
65047	65047C	750 Kcmil-2 Str	09	27.50	3.62	3.20	3/8	442
65048	65048C	750 Kcmil-2 Str	10	30.00	3.62	3.20	3/8	442
65049	65049C	750 Kcmil-2 Str	11	32.50	3.62	3.20	3/8	442
65050	65050C	750 Kcmil-2 Str	12	35.00	3.62	3.20	3/8	442

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)