



Underground Submersible Single Side Connector

Features

- Dual rated for aluminum & copper conductors & supplied with pre-filled oxide inhibitor
- Abrasion, chemical UV resistance
- Range taking design
- UL486 D Listed for Sealed Wire Connectors
- Insulation high strength EPDM rubber with V0 flammability
- Encapsulated in rubber with a nominal thickness and high dielectric strength



Applications

- Use as end to end splice or reducer
- Used in lighting & underground power distribution

Standard Material

- Aluminum

Standard Finish

- EPDM insulation

Certification

- cULus Listed (E313905)
- NEC: 230.46



Catalog ID	Wire Range	No of Port	Dimensions In Inches			Hex Size
			L	W	H	
70001	2/0-14 Sol/Str	02	1.81	2.46	2.10	3/16
70002	2/0-14 Sol/Str	03	2.66	2.46	2.10	3/16
70003	2/0-14 Sol/Str	04	3.50	2.46	2.10	3/16
70004	2/0-14 Sol/Str	05	4.35	2.46	2.10	3/16
70005	2/0-14 Sol/Str	06	5.20	2.46	2.10	3/16
70006	2/0-14 Sol/Str	07	6.04	2.46	2.10	3/16
70007	2/0-14 Sol/Str	08	6.89	2.46	2.10	3/16
70008	2/0-14 Sol/Str	09	7.73	2.46	2.10	3/16
70009	2/0-14 Sol/Str	10	8.58	2.46	2.10	3/16
70010	2/0-14 Sol/Str	11	9.43	2.46	2.10	3/16
70011	2/0-14 Sol/Str	12	10.27	2.46	2.10	3/16
70012	350 Kcmil-12 Sol/Str	02	2.40	4.19	3.21	5/16
70013	350 Kcmil-12 Sol/Str	03	3.60	4.19	3.21	5/16
70014	350 Kcmil-12 Sol/Str	04	4.76	4.19	3.21	5/16
70015	350 Kcmil-12 Sol/Str	05	5.92	4.19	3.21	5/16
70016	350 Kcmil-12 Sol/Str	06	7.08	4.19	3.21	5/16
70017	350 Kcmil-12 Sol/Str	07	8.24	4.19	3.21	5/16
70018	350 Kcmil-12 Sol/Str	08	9.40	4.19	3.21	5/16
70019	350 Kcmil-12 Sol/Str	09	10.56	4.19	3.21	5/16
70020	350 Kcmil-12 Sol/Str	10	11.72	4.19	3.21	5/16
70021	350 Kcmil-12 Sol/Str	11	12.88	4.19	3.21	5/16
70022	350 Kcmil-12 Sol/Str	12	14.05	4.19	3.21	5/16
70023	600 Kcmil-12 Sol/Str	02	3.22	5.14	3.52	5/16
70024	600 Kcmil-12 Sol/Str	03	4.92	5.14	3.52	5/16
70025	600 Kcmil-12 Sol/Str	04	6.63	5.14	3.52	5/16
70026	600 Kcmil-12 Sol/Str	05	8.34	5.14	3.52	5/16
70027	600 Kcmil-12 Sol/Str	06	10.05	5.14	3.52	5/16
70028	600 Kcmil-12 Sol/Str	07	11.76	5.14	3.52	5/16
70029	600 Kcmil-12 Sol/Str	08	13.47	5.14	3.52	5/16
70030	600 Kcmil-12 Sol/Str	09	15.18	5.14	3.52	5/16
70031	600 Kcmil-12 Sol/Str	10	16.88	5.14	3.52	5/16
70032	600 Kcmil-12 Sol/Str	11	18.59	5.14	3.52	5/16
70033	600 Kcmil-12 Sol/Str	12	20.30	5.14	3.52	5/16
70034	750 Kcmil-12 Sol/Str	02	3.46	5.89	3.90	3/8
70035	750 Kcmil-12 Sol/Str	03	5.30	5.89	3.90	3/8
70036	750 Kcmil-12 Sol/Str	04	7.13	5.89	3.90	3/8
70037	750 Kcmil-12 Sol/Str	05	8.96	5.89	3.90	3/8
70038	750 Kcmil-12 Sol/Str	06	10.79	5.89	3.90	3/8
70039	750 Kcmil-12 Sol/Str	07	12.62	5.89	3.90	3/8
70040	750 Kcmil-12 Sol/Str	08	14.45	5.89	3.90	3/8
70041	750 Kcmil-12 Sol/Str	09	16.28	5.89	3.90	3/8
70042	750 Kcmil-12 Sol/Str	10	18.11	5.89	3.90	3/8
70043	750 Kcmil-12 Sol/Str	11	19.94	5.89	3.90	3/8
70044	750 Kcmil-12 Sol/Str	12	21.77	5.89	3.90	3/8

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)