

Series E® Set Screw Aluminum Conduit Body with Cover and Gasket (EMT) Type LC

Features

- Set screw LC type with cover and gasket
- Hubs
- Suitable for use in concrete
- Suitable for use in wet locations

Applications

- Provides access to conductors for pulling, splicing and maintenance

Standard Material

- Copper free aluminum die-cast
- Cover: Stamped aluminum
- Screw: Steel
- Gasket: Neoprene rubber

Standard Finish


- Premium epoxy powder coated

Certification

- UL® listed (E520149)
- NEMA 3R
- 2020 NEC® compliant



LISTED
OUTLET BOX
E520149



Catalog ID	Trade Size	Conductor Size		Dimensions In Inches			Volume In³
		Max Number	Max Size	L	W	H	
ELC050SSCG	1/2	1	6 AWG	4.93	1.32	1.58	4.30
ELC075SSCG	3/4	2	6 AWG	5.67	1.53	1.79	7.30
ELC100SSCG	1	3	6 AWG	6.46	1.75	2.14	12.3
ELC125SSCG	1-1/4	3	2 AWG	8.27	2.50	2.72	32.3
ELC150SSCG	1-1/2	3	2 AWG	8.27	2.50	2.92	33.8
ELC200SSCG	2	3	2/0 AWG	10.24	3.14	3.49	69.8
ELC250SSCG	2-1/2	3	4/0 AWG	13.45	4.45	4.26	153.0
ELC300SSCG	3	3	250 MCM	13.45	4.45	4.90	182.5
ELC350SSCG	3-1/2	3	350 MCM	16.00	5.42	5.68	304.9
ELC400SSCG	4	4	350 MCM	16.00	5.42	5.75	308.0

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Series E® Set Screw Aluminum Conduit Body (EMT) Type LC

Features

- Set screw LC type
- Hubs
- Suitable for use in concrete

Applications

- Provides access to conductors for pulling, splicing and maintenance

Standard Material

- Copper free aluminum die-cast
- Screw: Steel

Standard Finish


- Premium epoxy powder coated

Certification

- UL® listed (E520149)
- NEMA 3R
- 2020 NEC® compliant



LISTED
OUTLET BOX
E520149



Catalog ID	Trade Size	Conductor Size		Dimensions In Inches			Volume In³
		Max Number	Max Size	L	W	H	
ELC050SS	1/2	1	6 AWG	4.93	1.32	1.34	4.30
ELC075SS	3/4	2	6 AWG	5.67	1.53	1.54	7.30
ELC100SS	1	3	6 AWG	6.46	1.75	1.89	12.3
ELC125SS	1-1/4	3	2 AWG	8.27	2.50	2.48	32.3
ELC150SS	1-1/2	3	2 AWG	8.27	2.50	2.68	33.8
ELC200SS	2	3	2/0 AWG	10.24	3.14	3.25	69.8
ELC250SS	2-1/2	3	4/0 AWG	13.45	4.45	4.00	153.0
ELC300SS	3	3	250 MCM	13.45	4.45	4.66	182.5
ELC350SS	3-1/2	3	350 MCM	16.00	5.42	5.43	304.9
ELC400SS	4	4	350 MCM	16.00	5.42	5.51	308.0

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)