

Series E® Combination Aluminum Conduit Body with Cover and Gasket (EMT/Rigid/IMC) Type LB

Features

- Threaded LB type with cover and gasket
- NPT hubs with set screw
- Suitable for use in concrete
- Suitable for use in wet locations

Applications

- Provides access to conductors for pulling, splicing and maintenance

Standard Material

- Copper free aluminum die-cast
- Cover: Stamped aluminum
- Screw: Steel
- Gasket: Neoprene rubber

Standard Finish


- Premium epoxy powder coated

Certification

- UL® listed (E520149)
- NEMA 3R
- 2020 NEC® compliant



LISTED
OUTLET BOX
E520149



Catalog ID	Trade Size	Conductor Size		Dimensions In Inches			Volume In³
		Max Number	Max Size	L	W	H	
ELB050CCCG	1/2	1	6 AWG	4.39	1.32	2.25	4.30
ELB075CCCG	3/4	2	6 AWG	5.17	1.53	2.46	7.30
ELB100CCCG	1	3	6 AWG	6.00	1.75	2.92	12.3
ELB125CCCG	1-1/4	3	2 AWG	7.76	2.50	3.70	32.3
ELB150CCCG	1-1/2	3	2 AWG	7.76	2.50	3.90	33.8
ELB200CCCG	2	3	2/0 AWG	9.85	3.14	4.46	71.3
ELB250CCCG	2-1/2	3	4/0 AWG	12.84	4.45	5.46	153.0
ELB300CCCG	3	3	250 MCM	12.84	4.45	6.63	182.5
ELB350CCCG	3-1/2	3	350 MCM	15.45	5.42	7.00	304.9
ELB400CCCG	4	4	350 MCM	15.45	5.42	7.25	308.0

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Series E® Combination Aluminum Conduit Body (EMT/Rigid/IMC) Type LB

Features

- Threaded LB type
- NPT hubs with set screw
- Suitable for use in concrete

Applications

- Provides access to conductors for pulling, splicing and maintenance

Standard Material

- Copper free aluminum die-cast
- Screw: Steel

Standard Finish


- Premium epoxy powder coated

Certification

- UL® listed (E520149)
- NEMA 3R
- 2020 NEC® compliant



LISTED
OUTLET BOX
E520149



Catalog ID	Trade Size	Conductor Size		Dimensions In Inches			Volume In³
		Max Number	Max Size	L	W	H	
ELB050CC	1/2	1	6 AWG	4.39	1.32	2.00	4.30
ELB075CC	3/4	2	6 AWG	5.17	1.53	2.21	7.30
ELB100CC	1	3	6 AWG	6.00	1.75	2.68	12.3
ELB125CC	1-1/4	3	2 AWG	7.76	2.50	3.46	32.3
ELB150CC	1-1/2	3	2 AWG	7.76	2.50	3.66	33.8
ELB200CC	2	3	2/0 AWG	9.85	3.14	4.22	71.3
ELB250CC	2-1/2	3	4/0 AWG	12.84	4.45	5.21	153.0
ELB300CC	3	3	250 MCM	12.84	4.45	6.39	182.5
ELB350CC	3-1/2	3	350 MCM	15.45	5.42	6.77	304.9
ELB400CC	4	4	350 MCM	15.45	5.42	7.00	308.0

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)