

## Series E® Combination Aluminum Conduit Body with Cover and Gasket (EMT/Rigid/IMC) Type LL

### Features

- Threaded LL type with cover and gasket
- NPT hubs with set screw
- Suitable for use in concrete
- Suitable for use in wet locations

### Applications

- Provides access to conductors for pulling, splicing and maintenance

### Standard Material

- Copper free aluminum die-cast
- Cover: Stamped aluminum
- Screw: Steel
- Gasket: Neoprene rubber

### Standard Finish


- Premium epoxy powder coated

### Certification

- UL® listed (E520149)
- NEMA 3R
- 2020 NEC® compliant



**LISTED**  
**OUTLET BOX**  
**E520149**



| Catalog ID | Trade Size | Conductor Size |          | Dimensions In Inches |      |      | Volume In³ |
|------------|------------|----------------|----------|----------------------|------|------|------------|
|            |            | Max Number     | Max Size | L                    | W    | H    |            |
| ELL050CCCG | 1/2        | 1              | 6 AWG    | 4.39                 | 1.91 | 1.58 | 4.30       |
| ELL075CCCG | 3/4        | 2              | 6 AWG    | 5.17                 | 2.23 | 1.79 | 7.30       |
| ELL100CCCG | 1          | 3              | 6 AWG    | 6.00                 | 2.48 | 2.14 | 12.3       |
| ELL125CCCG | 1-1/4      | 3              | 2 AWG    | 7.76                 | 3.42 | 2.72 | 32.3       |
| ELL150CCCG | 1-1/2      | 3              | 2 AWG    | 7.76                 | 3.42 | 2.92 | 33.8       |
| ELL200CCCG | 2          | 3              | 2/0 AWG  | 9.85                 | 4.00 | 3.49 | 71.3       |
| ELL250CCCG | 2-1/2      | 3              | 4/0 AWG  | 12.84                | 6.00 | 4.26 | 153.0      |
| ELL300CCCG | 3          | 3              | 250 MCM  | 12.84                | 6.00 | 4.90 | 182.5      |
| ELL350CCCG | 3-1/2      | 3              | 350 MCM  | 15.45                | 6.40 | 5.68 | 304.9      |
| ELL400CCCG | 4          | 4              | 350 MCM  | 15.45                | 6.40 | 5.75 | 308.0      |

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

## Series E® Combination Aluminum Conduit Body (EMT/Rigid/IMC) Type LL

### Features

- Threaded LL type
- NPT hubs with set screw
- Suitable for use in concrete

### Applications

- Provides access to conductors for pulling, splicing and maintenance

### Standard Material

- Copper free aluminum die-cast
- Screw: Steel

### Standard Finish


- Premium epoxy powder coated

### Certification

- UL® listed (E520149)
- NEMA 3R
- 2020 NEC® compliant



**LISTED**  
**OUTLET BOX**  
**E520149**



| Catalog ID | Trade Size | Conductor Size |          | Dimensions In Inches |      |      | Volume In³ |
|------------|------------|----------------|----------|----------------------|------|------|------------|
|            |            | Max Number     | Max Size | L                    | W    | H    |            |
| ELL050CC   | 1/2        | 1              | 6 AWG    | 4.39                 | 1.91 | 1.34 | 4.30       |
| ELL075CC   | 3/4        | 2              | 6 AWG    | 5.17                 | 2.23 | 1.54 | 7.30       |
| ELL100CC   | 1          | 3              | 6 AWG    | 6.00                 | 2.48 | 1.89 | 12.3       |
| ELL125CC   | 1-1/4      | 3              | 2 AWG    | 7.76                 | 3.42 | 2.48 | 32.3       |
| ELL150CC   | 1-1/2      | 3              | 2 AWG    | 7.76                 | 3.42 | 2.68 | 33.8       |
| ELL200CC   | 2          | 3              | 2/0 AWG  | 9.85                 | 4.00 | 3.25 | 71.3       |
| ELL250CC   | 2-1/2      | 3              | 4/0 AWG  | 12.84                | 6.00 | 4.00 | 153.0      |
| ELL300CC   | 3          | 3              | 250 MCM  | 12.84                | 6.00 | 4.66 | 182.5      |
| ELL350CC   | 3-1/2      | 3              | 350 MCM  | 15.45                | 6.40 | 5.43 | 304.9      |
| ELL400CC   | 4          | 4              | 350 MCM  | 15.45                | 6.40 | 5.51 | 308.0      |

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)