

Series E® Combination Aluminum Conduit Body with Cover and Gasket (EMT/Rigid/IMC) Type LR

Features

- Threaded LR type cover and gasket
- NPT hubs with set screw
- Suitable for use in concrete

Applications

- Provides access to conductors for pulling, splicing and maintenance

Standard Material


- Copper free aluminum die-cast
- Cover: Stamped aluminum
- Screw: Steel
- Gasket: Neoprene rubber

Standard Finish

- Premium epoxy powder coated

Certification

- UL® listed (E520149)
- NEMA 3R
- 2020 NEC® compliant



Catalog ID	Trade Size	Conductor Size		Dimensions In Inches			Volume In³
		Max Number	Max Size	L	W	H	
ELR050CCCG	1/2	1	6 AWG	4.39	1.91	1.58	4.30
ELR075CCCG	3/4	2	6 AWG	5.17	2.23	1.79	7.30
ELR100CCCG	1	3	6 AWG	6.00	2.48	2.14	12.3
ELR125CCCG	1-1/4	3	2 AWG	7.76	3.42	2.72	32.3
ELR150CCCG	1-1/2	3	2 AWG	7.76	3.42	2.92	33.8
ELR200CCCG	2	3	2/0 AWG	9.85	4.00	3.49	71.3
ELR250CCCG	2-1/2	3	4/0 AWG	12.84	6.00	4.26	153.0
ELR300CCCG	3	3	250 MCM	12.84	6.00	4.90	182.5
ELR350CCCG	3-1/2	3	350 MCM	15.45	6.40	5.68	304.9
ELR400CCCG	4	4	350 MCM	15.45	6.40	5.75	308.0

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Series E® Combination Aluminum Conduit Body (EMT/Rigid/IMC) Type LR

Features

- Threaded LR type
- NPT hubs with set screw
- Suitable for use in concrete

Applications

- Provides access to conductors for pulling, splicing and maintenance

Standard Material


- Copper free aluminum die-cast
- Screw: Steel

Standard Finish

- Premium epoxy powder coated

Certification

- UL® listed (E520149)
- NEMA 3R
- 2020 NEC® compliant



Catalog ID	Trade Size	Conductor Size		Dimensions In Inches			Volume In³
		Max Number	Max Size	L	W	H	
ELR050CC	1/2	1	6 AWG	4.39	1.91	1.58	4.30
ELR075CC	3/4	2	6 AWG	5.17	2.23	1.79	7.30
ELR100CC	1	3	6 AWG	6.00	2.48	2.14	12.3
ELR125CC	1-1/4	3	2 AWG	7.76	3.42	2.72	32.3
ELR150CC	1-1/2	3	2 AWG	7.76	3.42	2.92	33.8
ELR200CC	2	3	2/0 AWG	9.85	4.00	3.49	71.3
ELR250CC	2-1/2	3	4/0 AWG	12.84	6.00	4.26	153.0
ELR300CC	3	3	250 MCM	12.84	6.00	4.90	182.5
ELR350CC	3-1/2	3	350 MCM	15.45	6.40	5.68	304.9
ELR400CC	4	4	350 MCM	15.45	6.40	5.75	308.0

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)