

Series E® Combination Aluminum Conduit Body with Cover and Gasket (EMT/Rigid/IMC) Type LT

Features

- Threaded LT type with cover and gasket
- NPT hubs with set screw
- Suitable for use in concrete
- Suitable for use in wet locations

Applications

- Provides access to conductors for pulling, splicing and maintenance

Standard Material

- Copper free aluminum die-cast
- Cover: Stamped aluminum
- Screw: Steel
- Gasket: Neoprene rubber

Standard Finish


- Premium epoxy powder coated

Certification

- UL® listed (E520149)
- NEMA 3R
- 2020 NEC® compliant



LISTED
OUTLET BOX
E520149



Catalog ID	Trade Size	Conductor Size		Dimensions In Inches			Volume In³
		Max Number	Max Size	L	W	H	
ELT050CCCG	1/2	1	6 AWG	4.93	1.91	1.58	4.30
ELT075CCCG	3/4	2	6 AWG	5.67	2.23	1.79	7.30
ELT100CCCG	1	3	6 AWG	6.46	2.48	2.14	12.3
ELT125CCCG	1-1/4	3	2 AWG	8.27	3.42	2.72	32.3
ELT150CCCG	1-1/2	3	2 AWG	8.27	3.42	2.92	33.8
ELT200CCCG	2	3	2/0 AWG	10.24	4.00	3.49	71.3
ELT250CCCG	2-1/2	3	4/0 AWG	13.45	6.00	4.26	153.0
ELT300CCCG	3	3	250 MCM	13.45	6.00	4.90	182.5
ELT350CCCG	3-1/2	3	350 MCM	16.00	6.40	5.68	304.9
ELT400CCCG	4	4	350 MCM	16.00	6.40	5.75	308.0

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Series E® Combination Aluminum Conduit Body (EMT/Rigid/IMC) Type LT

Features

- Threaded LT type
- NPT hubs with set screw
- Suitable for use in concrete

Applications

- Provides access to conductors for pulling, splicing and maintenance

Standard Material

- Copper free aluminum die-cast
- Screw: Steel

Standard Finish


- Premium epoxy powder coated

Certification

- UL® listed (E520149)
- NEMA 3R
- 2020 NEC® compliant



LISTED
OUTLET BOX
E520149



Catalog ID	Trade Size	Conductor Size		Dimensions In Inches			Volume In³
		Max Number	Max Size	L	W	H	
ELT050CC	1/2	1	6 AWG	4.93	1.91	1.34	4.30
ELT075CC	3/4	2	6 AWG	5.67	2.23	1.54	7.30
ELT100CC	1	3	6 AWG	6.46	2.48	1.89	12.3
ELT125CC	1-1/4	3	2 AWG	8.27	3.42	2.48	32.3
ELT150CC	1-1/2	3	2 AWG	8.27	3.42	2.68	33.8
ELT200CC	2	3	2/0 AWG	10.24	4.00	3.25	71.3
ELT250CC	2-1/2	3	4/0 AWG	13.45	6.00	4.00	153.0
ELT300CC	3	3	250 MCM	13.45	6.00	4.66	182.5
ELT350CC	3-1/2	3	350 MCM	16.00	6.40	5.43	304.9
ELT400CC	4	4	350 MCM	16.00	6.40	5.51	308.0

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)