Dry-Shield® Boxes

Dry-Shield®1 Gang Box 3 Hole Threaded Outlets

- · Durable die-cast aluminum construction provides a long product life.
- 1/2", 3/4" and 1" NPT threaded Outlets.
- · Precision cast and machined surfaces allow safer wire-pulling.
- · Mounting lugs for a variety of mounting methods.
- · Available in gray, black, bronze and white.

Applications

- For use as a weatherproof junction box in damp or wet locations when combined with a weatherproof cover.
- Features an accessible wiring chamber that provides a convenient location to maintain or change a system, make splices, and pull conductors.
- · Junction box to branch conduits.

Standard Material • Die Cast Aluminum

Standard Finish · Powder Coated

Packaging






OUTLET BOX

E520149









Certification

- cULus Listed (E520149)
- · Boxes and covers suitable for use in wet locations
- NEMA 3R Rated
- Complies with NEC Article 409.6(B)(1)

Catalog ID	Size	Outlet	Α	В	С	Volume In ³	Color
W1B503	1/2	3-1/2	4.50	2.80	2.10	18	
W1B503BL	1/2	3-1/2	4.50	2.80	2.10	18	
W1B503AB	1/2	3-1/2	4.50	2.80	2.10	18	
W1B503WH	1/2	3-1/2	4.50	2.80	2.10	18	
W1B753	3/4	3-3/4	4.50	2.80	2.10	18	
W1B753BL	3/4	3-3/4	4.50	2.80	2.10	18	
W1B753AB	3/4	3-3/4	4.50	2.80	2.10	18	
W1B753WH	3/4	3-3/4	4.50	2.80	2.10	18	
W1B1003	1	3-1	4.50	2.80	2.10	17	
W1B1003BL	1	3-1	4.50	2.80	2.10	17	
W1B1003AB	1	3-1	4.50	2.80	2.10	17	
W1B1003WH	1	3-1	4.50	2.80	2.10	17	

Dry-Shield® 1 Gang Deep Box 3 Hole Threaded Outlets

Features

- · Durable die-cast aluminum construction provides a long product life.
- 1/2", 3/4" and 1" NPT threaded Outlets.
- Precision cast and machined surfaces allow safer wire-pulling.
- · Mounting lugs for a variety of mounting methods.
- · Available in gray, black, bronze and white.

Applications

- For use as a weatherproof junction box in damp or wet locations when combined with a weatherproof cover.
- Features an accessible wiring chamber that provides a convenient location to maintain or change a system, make splices, and pull conductors.
- Junction box to branch conduits.

Standard Material • Die Cast Aluminum

Standard Finish · Powder Coated

Packaging Shrink Packed


Blister Carded



E520149

RoHS LISTED OUTLET BOX





Certifica	uon	
• cl II us I	isted	(F520149)

- · Boxes and covers suitable for use in wet locations
- NFMA 3R Rated
- Complies with NEC Article 409.6(B)(1)

Catalog ID	Size	Outlet	Α	В	С	Volume In ³	Color
W1DB503	1/2	3-1/2	4.50	2.80	2.70	24	
W1DB503BL	1/2	3-1/2	4.50	2.80	2.70	24	
W1DB503AB	1/2	3-1/2	4.50	2.80	2.70	24	
W1DB503WH	1/2	3-1/2	4.50	2.80	2.70	24	
W1DB753	3/4	3-3/4	4.50	2.80	2.70	24	
W1DB753BL	3/4	3-3/4	4.50	2.80	2.70	24	
W1DB753AB	3/4	3-3/4	4.50	2.80	2.70	24	
W1DB753WH	3/4	3-3/4	4.50	2.80	2.70	24	
W1DB1003	1	3-1	4.50	2.80	2.70	24	
W1DB1003BL	1	3-1	4.50	2.80	2.70	24	
W1DB1003AB	1	3-1	4.50	2.80	2.70	24	
W1DB1003WH	1	3-1	4.50	2.80	2.70	24	

US: (732) 479 0469 www.oec-americas.com sales@oec-americas.com