

Dry-Shield® 1 Gang Box 5 Hole Threaded Outlets

Features

- Durable die-cast aluminum construction provides a long product life.
- 1 1/2" and 3/4" NPT threaded Outlets.
- Precision cast and machined surfaces allow safer wire-pulling.
- Mounting lugs for a variety of mounting methods.
- Available in gray, black, bronze and white.

Applications

- For use as a weatherproof junction box in damp or wet locations when combined with a weatherproof cover.
- Features an accessible wiring chamber that provides a convenient location to maintain or change a system, make splices, and pull conductors.
- Junction box to branch conduits.

Standard Material


- Die Cast Aluminum

Standard Finish

- Powder Coated

Packaging

- Shrink Packed
- Blister Carded



Certification

- cULus Listed (E520149)
- Boxes and covers suitable for use in wet locations
- NEMA 3R Rated
- Complies with NEC Article 409.6(B)(1)

Catalog ID	Size	Outlet	A	B	C	Volume In³	Color
W1B505	1/2	5-1/2	4.50	2.80	2.10	17	
W1B505BL	1/2	5-1/2	4.50	2.80	2.10	17	
W1B505AB	1/2	5-1/2	4.50	2.80	2.10	17	
W1B505WH	1/2	5-1/2	4.50	2.80	2.10	17	
W1B755	3/4	5-3/4	4.50	2.80	2.10	17	
W1B755BL	3/4	5-3/4	4.50	2.80	2.10	17	
W1B755AB	3/4	5-3/4	4.50	2.80	2.10	17	
W1B755WH	3/4	5-3/4	4.50	2.80	2.10	17	

Dry-Shield® 1 Gang Box 5 Hole Threaded Outlets HV (Type-X)

Features

- Durable die-cast aluminum construction provides a long product life.
- 1/2", 3/4" and 1" NPT threaded Outlets.
- Precision cast and machined surfaces allow safer wire-pulling.
- Mounting lugs for a variety of mounting methods.
- Available in gray, black, bronze and white.

Applications

- For use as a weatherproof junction box in damp or wet locations when combined with a weatherproof cover.
- Features an accessible wiring chamber that provides a convenient location to maintain or change a system, make splices, and pull conductors.
- Junction box to branch conduits.

Standard Material


- Die Cast Aluminum

Standard Finish

- Powder Coated

Packaging

- Shrink Packed
- Blister Carded



Certification

- cULus Listed (E520149)
- Boxes and covers suitable for use in wet locations
- NEMA 3R Rated
- Complies with NEC Article 409.6(B)(1)

Catalog ID	Size	Outlet	A	B	C	Volume In³	Color
W1B505X	1/2	5-1/2	4.50	2.80	2.10	16	
W1B505XBL	1/2	5-1/2	4.50	2.80	2.10	16	
W1B505XAB	1/2	5-1/2	4.50	2.80	2.10	16	
W1B505XWH	1/2	5-1/2	4.50	2.80	2.10	16	
W1B755X	3/4	5-3/4	4.50	2.80	2.10	16	
W1B755XBL	3/4	5-3/4	4.50	2.80	2.10	16	
W1B755XAB	3/4	5-3/4	4.50	2.80	2.10	16	
W1B755XWH	3/4	5-3/4	4.50	2.80	2.10	16	
W1B1005X	1	5-1	4.50	2.80	2.10	16	
W1B1005XBL	1	5-1	4.50	2.80	2.10	16	
W1B1005XAB	1	5-1	4.50	2.80	2.10	16	
W1B1005XWH	1	5-1	4.50	2.80	2.10	16	