

## Dry-Shield® 1 Gang Deep Box 5 Hole Threaded Outlets-HV (Type-X)

### Features

- Durable die-cast aluminum construction provides a long product life.
- 1/2", 3/4" and 1" NPT threaded Outlets.
- Precision cast and machined surfaces allow safer wire-pulling.
- Mounting lugs for a variety of mounting methods.
- Available in gray, black, bronze and white.

### Applications

- For use as a weatherproof junction box in damp or wet locations when combined with a weatherproof cover.
- Features an accessible wiring chamber that provides a convenient location to maintain or change a system, make splices, and pull conductors.
- Junction box to branch conduits.

### Standard Material

- Die Cast Aluminum

### Standard Finish


- Powder Coated

### Packaging

- Shrink Packed
- Blister Carded

### Certification

- cULus Listed (E520149)
- Boxes and covers suitable for use in wet locations
- NEMA 3R Rated
- Complies with NEC Article 409.6(B)(1)



Catalog ID	Size	Outlet	A	B	C	Volume In <sup>3</sup>	Color
W1DB505X	1/2	5-1/2	4.50	2.80	2.70	23	Gray
W1DB505XBL	1/2	5-1/2	4.50	2.80	2.70	23	Black
W1DB505XAB	1/2	5-1/2	4.50	2.80	2.70	23	Bronze
W1DB505XWH	1/2	5-1/2	4.50	2.80	2.70	23	White
W1DB755X	3/4	5-3/4	4.50	2.80	2.70	24	Gray
W1DB755XBL	3/4	5-3/4	4.50	2.80	2.70	24	Black
W1DB755XAB	3/4	5-3/4	4.50	2.80	2.70	24	Bronze
W1DB755XWH	3/4	5-3/4	4.50	2.80	2.70	24	White
W1DB1005X	1	5-1	4.50	2.80	2.70	22	Gray
W1DB1005XBL	1	5-1	4.50	2.80	2.70	22	Black
W1DB1005XAB	1	5-1	4.50	2.80	2.70	22	Bronze
W1DB1005XWH	1	5-1	4.50	2.80	2.70	22	White