

## Dry-Shield® 2 Gang Box 6 Hole Threaded Outlets-XV (Universal)

### Features

- Durable die-cast aluminum construction provides a long product life.
- 1/2" and 3/4" NPT threaded Outlets.
- Precision cast and machined surfaces allow safer wire-pulling.
- Mounting lugs for a variety of mounting methods.
- Available in gray, black, bronze and white.

### Applications

- For use as a weatherproof junction box in damp or wet locations when combined with a weatherproof cover.
- Features an accessible wiring chamber that provides a convenient location to maintain or change a system, make splices, and pull conductors.
- Junction box to branch conduits.

### Standard Material

- Die Cast Aluminum

### Standard Finish


- Powder Coated

### Packaging

- Shrink Packed
- Blister Carded

### Certification

- cULus Listed (E520149)
- Boxes and covers suitable for use in wet locations
- NEMA 3R Rated
- Complies with NEC Article 409.6(B)(1)



Catalog ID	Size	Outlet	A	B	C	Volume In³	Color
W2B506X	1/2	6-1/2	4.50	4.50	2.10	29	Gray
W2B506XBL	1/2	6-1/2	4.50	4.50	2.10	29	Black
W2B506XAB	1/2	6-1/2	4.50	4.50	2.10	29	Bronze
W2B506XWH	1/2	6-1/2	4.50	4.50	2.10	29	White
W2B756X	3/4	6-3/4	4.50	4.50	2.10	29	Gray
W2B756XBL	3/4	6-3/4	4.50	4.50	2.10	29	Black
W2B756XAB	3/4	6-3/4	4.50	4.50	2.10	29	Bronze
W2B756XWH	3/4	6-3/4	4.50	4.50	2.10	29	White

## Dry-Shield® 2 Gang Box 7 Hole Threaded Outlets (Universal)

### Features

- Durable die-cast aluminum construction provides a long product life.
- 1/2" and 3/4" NPT threaded Outlets.
- Precision cast and machined surfaces allow safer wire-pulling.
- Mounting lugs for a variety of mounting methods.
- Available in gray, black, bronze and white.

### Applications

- For use as a weatherproof junction box in damp or wet locations when combined with a weatherproof cover.
- Features an accessible wiring chamber that provides a convenient location to maintain or change a system, make splices, and pull conductors.
- Junction box to branch conduits.

### Standard Material

- Die Cast Aluminum

### Standard Finish


- Powder Coated

### Packaging

- Shrink Packed
- Blister Carded

### Certification

- cULus Listed (E520149)
- Boxes and covers suitable for use in wet locations
- NEMA 3R Rated
- Complies with NEC Article 409.6(B)(1)



Catalog ID	Size	Outlet	A	B	C	Volume In³	Color
W2B507U	1/2	7-1/2	4.50	4.50	2.10	29	Gray
W2B507UBL	1/2	7-1/2	4.50	4.50	2.10	29	Black
W2B507UAB	1/2	7-1/2	4.50	4.50	2.10	29	Bronze
W2B507UWH	1/2	7-1/2	4.50	4.50	2.10	29	White
W2B757U	3/4	7-3/4	4.50	4.50	2.10	29	Gray
W2B757UBL	3/4	7-3/4	4.50	4.50	2.10	29	Black
W2B757UAB	3/4	7-3/4	4.50	4.50	2.10	29	Bronze
W2B757UWH	3/4	7-3/4	4.50	4.50	2.10	29	White