

## Dry-Shield® 2 Gang Box 7 Hole Threaded Outlets-XV (Universal)

### Features

- Durable die-cast aluminum construction provides a long product life.
- 1/2" and 3/4" NPT threaded Outlets.
- Precision cast and machined surfaces allow safer wire-pulling.
- Mounting lugs for a variety of mounting methods.
- Available in gray, black, bronze and white.

### Applications

- For use as a weatherproof junction box in damp or wet locations when combined with a weatherproof cover.
- Features an accessible wiring chamber that provides a convenient location to maintain or change a system, make splices, and pull conductors.
- Junction box to branch conduits.

### Standard Material

- Die Cast Aluminum

### Standard Finish


- Powder Coated

### Packaging

- Shrink Packed
- Blister Carded

### Certification

- cULus Listed (E520149)
- Boxes and covers suitable for use in wet locations
- NEMA 3R Rated
- Complies with NEC Article 409.6(B)(1)



Catalog ID	Size	Outlet	A	B	C	Volume In³	Color
W2B507X	1/2	7-1/2	4.50	4.50	2.10	29	Gray
W2B507XBL	1/2	7-1/2	4.50	4.50	2.10	29	Black
W2B507XAB	1/2	7-1/2	4.50	4.50	2.10	29	Bronze
W2B507XWH	1/2	7-1/2	4.50	4.50	2.10	29	White
W2B757X	3/4	7-3/4	4.50	4.50	2.10	29	Gray
W2B757XBL	3/4	7-3/4	4.50	4.50	2.10	29	Black
W2B757XAB	3/4	7-3/4	4.50	4.50	2.10	29	Bronze
W2B757XWH	3/4	7-3/4	4.50	4.50	2.10	29	White

## Dry-Shield® 2 Gang Deep Box 7 Hole Threaded Outlets-HV

### Features

- Durable die-cast aluminum construction provides a long product life.
- 1/2", 3/4" and 1" NPT threaded Outlets.
- Precision cast and machined surfaces allow safer wire-pulling.
- Mounting lugs for a variety of mounting methods.
- Available in gray, black, bronze and white.

### Applications

- For use as a weatherproof junction box in damp or wet locations when combined with a weatherproof cover.
- Features an accessible wiring chamber that provides a convenient location to maintain or change a system, make splices, and pull conductors.
- Junction box to branch conduits.

### Standard Material

- Die Cast Aluminum

### Standard Finish


- Powder Coated

### Packaging

- Shrink Packed
- Blister Carded

### Certification

- cULus Listed (E520149)
- Boxes and covers suitable for use in wet locations
- NEMA 3R Rated
- Complies with NEC Article 409.6(B)(1)



Catalog ID	Size	Outlet	A	B	C	Volume In³	Color
W2DB507X	1/2	7-1/2	4.50	4.50	2.70	29	Gray
W2DB507XBL	1/2	7-1/2	4.50	4.50	2.70	29	Black
W2DB507XAB	1/2	7-1/2	4.50	4.50	2.70	29	Bronze
W2DB507XWH	1/2	7-1/2	4.50	4.50	2.70	29	White
W2DB757X	3/4	7-3/4	4.50	4.50	2.70	24	Gray
W2DB757XBL	3/4	7-3/4	4.50	4.50	2.70	24	Black
W2DB757XAB	3/4	7-3/4	4.50	4.50	2.70	24	Bronze
W2DB757XWH	3/4	7-3/4	4.50	4.50	2.70	24	White
W2DB1007	1	7-1	4.50	4.50	2.70	35	Gray
W2DB1007BL	1	7-1	4.50	4.50	2.70	35	Black
W2DB1007AB	1	7-1	4.50	4.50	2.70	35	Bronze
W2DB1007WH	1	7-1	4.50	4.50	2.70	35	White