

Dry-Shield® 2 Gang Box 5 Hole Threaded Outlets - XV (Universal)

Features

- Durable die-cast aluminum construction provides a long product life.
- 1" NPT threaded Outlets.
- Precision cast and machined surfaces allow safer wire-pulling.
- Mounting lugs for a variety of mounting methods.
- Available in gray, black, bronze and white.

Applications

- For use as a weatherproof junction box in damp or wet locations when combined with a weatherproof cover.
- Features an accessible wiring chamber that provides a convenient location to maintain or change a system, make splices, and pull conductors.
- Junction box to branch conduits.

Standard Material

- Die Cast Aluminum

Standard Finish


- Powder Coated

Packaging

- Shrink Packed
- Blister Carded

Certification

- cULus Listed (E520149)
- Boxes and covers suitable for use in wet locations
- NEMA 3R Rated
- Complies with NEC Article 409.6(B)(1)



Catalog ID	Size	Outlet	A	B	C	Volume In³	Color
W2B1005X	1	5-1	4.50	4.50	2.10	30	Gray
W2B1005XBL	1	5-1	4.50	4.50	2.10	30	Black
W2B1005XAB	1	5-1	4.50	4.50	2.10	30	Bronze
W2B1005XWH	1	5-1	4.50	4.50	2.10	30	White

Dry-Shield® Round Gang Box 5 Hole Threaded Outlets

Features

- Durable die-cast aluminum construction provides a long product life.
- 1/2" and 3/4" NPT threaded Outlets.
- Precision cast and machined surfaces allow safer wire-pulling.
- Mounting lugs for a variety of mounting methods.
- Available in gray, black, bronze and white.

Applications

- For use as a weatherproof junction box in damp or wet locations when combined with a weatherproof cover.
- Features an accessible wiring chamber that provides a convenient location to maintain or change a system, make splices, and pull conductors.
- Junction box to branch conduits.

Standard Material


- Die Cast Aluminum

Standard Finish

- Powder Coated

Certification

- cULus Listed (E520149)
- Boxes and covers suitable for use in wet locations
- NEMA 3R Rated
- Complies with NEC Article 409.6(B)(1)



Catalog ID	Size	Outlet	A	B	C	Volume In³	Color
WRB505	1/2	5-1/2	5.50	4.50	1.40	16	Gray
WRB505BL	1/2	5-1/2	5.50	4.50	1.40	16	Black
WRB505AB	1/2	5-1/2	5.50	4.50	1.40	16	Bronze
WRB505WH	1/2	5-1/2	5.50	4.50	1.40	16	White
WRB755	3/4	5-3/4	5.50	4.50	1.40	16	Gray
WRB755BL	3/4	5-3/4	5.50	4.50	1.40	16	Black
WRB755AB	3/4	5-3/4	5.50	4.50	1.40	16	Bronze
WRB755WH	3/4	5-3/4	5.50	4.50	1.40	16	White