

## Dry-Shield® Round Extension Box 4 hole Threaded Outlets

### Features

- Durable die-cast aluminum construction provides a long product life.
- 1/2" NPT threaded Outlets
- Precision cast and machined surfaces allow safer wire-pulling.
- Available in gray, black, bronze and white.

### Applications

- UL listed for wet location
- For use with OEC Dry-Shield weatherproof round gang box
- Increased cubic capacity

### Standard Material

- Die Cast Aluminum

### Standard Finish


- Powder Coated

### Certification

- cULus Listed (E520149)
- Boxes and covers suitable for use in wet locations
- NEMA 3R Rated
- Complies with NEC Article 409.6(B)(1)



**LISTED**  
**OUTLET BOX**  
**E520149**



| Catalog ID | Size | Outlet | A    | B    | C    | Volume In³ | Color |
|------------|------|--------|------|------|------|------------|-------|
| WREB504    | 1/2  | 4-1/2  | 2.70 | 2.70 | 1.60 | 16         |       |
| WREB504BL  | 1/2  | 4-1/2  | 2.70 | 2.70 | 1.60 | 16         |       |
| WREB504AB  | 1/2  | 4-1/2  | 2.70 | 2.70 | 1.60 | 16         |       |
| WREB504WH  | 1/2  | 4-1/2  | 2.70 | 2.70 | 1.60 | 16         |       |

## Dry-Shield® 1 Gang Extension Box 4 hole Threaded Outlets

### Features

- Durable die-cast aluminum construction provides a long product life.
- 1/2" NPT threaded Outlets
- Precision cast and machined surfaces allow safer wire-pulling.
- Available in gray, black, bronze and white.

### Applications

- UL listed for wet location
- For use with OEC Dry-Shield 1-gang weatherproof box
- Increased cubic capacity

### Standard Material

- Die Cast Aluminum

### Standard Finish


- Powder Coated

### Certification

- cULus Listed (E520149)
- Boxes and covers suitable for use in wet locations
- NEMA 3R Rated
- Complies with NEC Article 409.6(B)(1)



**LISTED**  
**OUTLET BOX**  
**E520149**



| Catalog ID | Size | Outlet | A    | B    | C    | Volume In³ | Color |
|------------|------|--------|------|------|------|------------|-------|
| W1EB504    | 1/2  | 4-1/2  | 4.72 | 2.87 | 1.32 | 16         |       |
| W1EB504BL  | 1/2  | 4-1/2  | 4.72 | 2.87 | 1.32 | 16         |       |
| W1EB504AB  | 1/2  | 4-1/2  | 4.72 | 2.87 | 1.32 | 16         |       |
| W1EB504WH  | 1/2  | 4-1/2  | 4.72 | 2.87 | 1.32 | 16         |       |