

Compression Connector (Steel) Uninsulated Throat

Catalog ID	Trade Size	Dimensions In Inches		
		A	B	C
FS151	1/2	1.80	1.00	0.40
FS152	3/4	1.90	1.25	0.45
FS153	1	2.18	1.52	0.50
FS154	1-1/4	2.44	1.90	0.60
FS155	1-1/2	2.45	2.13	0.62
FS156	2	2.78	2.61	0.65
FS157	2-1/2	4.24	3.45	0.73
FS158	3	4.41	4.00	0.73
FS159	3-1/2	4.50	4.57	0.73
FS160	4	4.55	5.00	0.73

Features

- For use when bonding EMT conduit to a box or enclosure
- Suitable for use in concrete
- Assembled with a steel locknut

Applications

- Use to join EMT to box or enclosure
- OEC 1/2" to 4" connectors provide secure concrete-tight connections
- Suitable for applications above 600V

Standard Material


- Steel

Standard Finish

- Zinc-electroplated

Certification

- 1/2"-2" cULus Listed (E539274)
- 2-1/2"-4" cULus Listed (E539275)
- NEMA FB1



Compression Connector (Steel) Insulated Throat

Catalog ID	Trade Size	Dimensions In Inches		
		A	B	C
FSI151	1/2	1.86	1.00	0.46
FSI152	3/4	1.96	1.25	0.50
FSI153	1	2.24	1.52	0.56
FSI154	1-1/4	2.50	1.90	0.66
FSI155	1-1/2	2.51	2.13	0.68
FSI156	2	2.84	2.61	0.70
FSI157	2-1/2	4.30	3.45	0.79
FSI158	3	4.47	4.00	0.79
FSI159	3-1/2	4.57	4.57	0.79
FSI160	4	4.61	5.00	0.79

Features

- For use when bonding EMT conduit to a box or enclosure
- Suitable for use in concrete
- Assembled with a steel locknut
- Assembled with insulated throat

Applications

- Use to join EMT to box or enclosure
- OEC 1/2" to 4" connectors provide secure concrete-tight connections
- Suitable for applications above 600V

Standard Material


- Steel

Standard Finish

- Zinc-electroplated

Certification

- 1/2"-2" cULus Listed (E539274)
- 2-1/2"-4" cULus Listed (E539275)
- NEMA FB1



Raintight Compression Connector (Steel) Uninsulated Throat

Catalog ID	Trade Size	Dimensions In Inches		
		A	B	C
FSRT151	1/2	1.80	1.00	0.40
FSRT152	3/4	1.90	1.25	0.45
FSRT153	1	2.18	1.52	0.50
FSRT154	1-1/4	2.44	1.90	0.60
FSRT155	1-1/2	2.45	2.13	0.62
FSRT156	2	2.78	2.61	0.65
FSRT157	2-1/2	4.24	3.45	0.73
FSRT158	3	4.41	4.00	0.73
FSRT159	3-1/2	4.50	4.57	0.73
FSRT160	4	4.55	5.00	0.73

Features

- For use when bonding EMT conduit to a box or enclosure
- Suitable for use in concrete & raintight
- Assembled with a gasket & steel locknut
- Couplings are designed to comply with UL Raintight test

Applications

- For use in wet locations to bond and secure EMT conduit to a box or enclosure
- OEC 1/2" to 4" connectors provide secure concrete-tight connections
- Suitable for applications above 600V

Standard Material


- Steel

Standard Finish

- Zinc-electroplated

Certification

- 1/2"-2" cULus Listed (E539274)
- 2-1/2"-4" cULus Listed (E539275)
- NEMA FB1



Raintight Compression Connector (Steel) Insulated Throat

Catalog ID	Trade Size	Dimensions In Inches		
		A	B	C
FSIRT151	1/2	1.86	1.00	0.46
FSIRT152	3/4	1.96	1.25	0.50
FSIRT153	1	2.24	1.52	0.56
FSIRT154	1-1/4	2.50	1.90	0.66
FSIRT155	1-1/2	2.51	2.13	0.67
FSIRT156	2	2.84	2.61	0.70
FSIRT157	2-1/2	4.30	3.45	0.79
FSIRT158	3	4.47	4.00	0.79
FSIRT159	3-1/2	4.56	4.57	0.79
FSIRT160	4	4.61	5.00	0.79

Features

- For use when bonding EMT conduit to a box or enclosure
- Suitable for use in concrete & raintight
- Assembled with a gasket & steel locknut
- Assembled with insulated throat
- Couplings are designed to comply with UL Raintight test

Applications

- For use in wet locations to bond and secure EMT conduit to a box or enclosure
- OEC 1/2" to 4" connectors provide secure concrete-tight connections
- Suitable for applications above 600V

Standard Material


- Steel

Standard Finish

- Zinc-electroplated

Certification

- 1/2"-2" cULus Listed (E539274)
- 2-1/2"-4" cULus Listed (E539275)
- NEMA FB1



All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Compression Coupling (Steel)

Catalog ID	Trade Size	Dimensions In Inches		
		A	B	C
FS611	1/2	1.67	1.00	0.71
FS612	3/4	1.69	1.25	0.93
FS613	1	1.99	1.52	1.17
FS614	1-1/4	2.15	1.90	1.52
FS615	1-1/2	2.37	2.13	1.75
FS616	2	2.64	2.61	2.20
FS617	2-1/2	3.70	3.45	2.89
FS618	3	4.36	4.00	3.52
FS619	3-1/2	4.89	4.57	4.02
FS620	4	5.15	5.00	4.52

Features

- Suitable for use in concrete
- Assembled with a steel nut
- Couplings are designed to comply with UL

Applications

- For use in wet locations to couple two ends of EMT conduit
- OEC 1/2" to 4" connectors provide secure concrete-tight connections
- Suitable for applications above 600V

Standard Material


- Steel

Standard Finish

- Zinc-electroplated

Certification

- 1/2"-2" cULus Listed (E539274)
- 2-1/2"-4" cULus Listed (E539275)
- NEMA FB1



Raintight Compression Coupling (Steel)

Catalog ID	Trade Size	Dimensions In Inches		
		A	B	C
FSRT611	1/2	1.67	1.00	0.71
FSRT612	3/4	1.69	1.25	0.93
FSRT613	1	1.99	1.52	1.17
FSRT614	1-1/4	2.15	1.90	1.52
FSRT615	1-1/2	2.37	2.13	1.75
FSRT616	2	2.64	2.61	2.20
FSRT617	2-1/2	3.70	3.45	2.89
FSRT618	3	4.36	4.00	3.52
FSRT619	3-1/2	4.89	4.57	4.02
FSRT620	4	5.15	5.00	4.52

Features

- Suitable for use in concrete
- Assembled with a steel nut
- Couplings are designed to comply with UL Raintight test

Applications

- For use in wet locations to couple two ends of EMT conduit
- OEC 1/2" to 4" connectors provide secure concrete-tight connections
- Suitable for applications above 600V

Standard Material


- Steel

Standard Finish

- Zinc-electroplated

Certification

- 1/2"-2" cULus Listed (E539274)
- 2-1/2"-4" cULus Listed (E539275)
- NEMA FB1



Set Screw Connector (Steel) Uninsulated Throat

Catalog ID	Trade Size	Dimensions In Inches		
		A	B	C
FS131	1/2	1.030	0.711	0.400
FS132	3/4	1.440	0.927	0.450
FS133	1	1.625	1.168	0.500
FS134	1-1/4	2.100	1.515	0.600
FS135	1-1/2	2.275	1.745	0.615
FS136	2	2.425	2.202	0.650
FS137	2-1/2	3.200	2.900	0.850
FS138	3	3.300	3.525	0.850
FS139	3-1/2	3.460	4.025	0.850
FS140	4	3.460	4.525	0.850

Features

- Assembled with a steel locknut
- Assembled with tri-combo head screw
- 1/2" to 1" trade sizes have one set-screw
- 1-1/4" to 4" trade sizes have two set-screws

Applications

- For use in wet locations to couple two ends of EMT conduit
- OEC 1/2" to 4" connectors provide secure concrete-tight connections
- Suitable for applications above 600V

Standard Material


- Steel

Standard Finish

- Zinc-electroplated

Certification

- 1/2"-2" cULus Listed (E539274)
- 2-1/2"-4" cULus Listed (E539275)
- NEMA FB1



Set Screw Connector (Steel) Insulated Throat

Catalog ID	Trade Size	Dimensions In Inches		
		A	B	C
FSI131	1/2	1.030	1.030	0.400
FSI132	3/4	1.440	1.300	0.450
FSI133	1	1.625	1.530	0.500
FSI134	1-1/4	2.100	1.970	0.600
FSI135	1-1/2	2.275	2.200	0.615
FSI136	2	2.425	2.660	0.650
FSI137	2-1/2	3.200	3.410	0.850
FSI138	3	3.300	4.010	0.850
FSI139	3-1/2	3.460	4.530	0.850
FSI140	4	3.460	5.160	0.850

Features

- Assembled with a steel locknut
- Assembled with tri-combo head screw
- 1/2" to 1" trade sizes have one set-screw
- 1-1/4" to 4" trade sizes have two set-screws
- Couplings are designed to comply with UL test

Applications

- For use in wet locations to couple two ends of EMT conduit
- OEC 1/2" to 4" connectors provide secure concrete-tight connections
- Suitable for applications above 600V

Standard Material


- Steel

Standard Finish

- Zinc-electroplated

Certification

- 1/2"-2" cULus Listed (E539274)
- 2-1/2"-4" cULus Listed (E539275)
- NEMA FB1



All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

EMT Connectors and Couplings

Set Screw Coupling (Steel)

Catalog ID	Trade Size	Dimensions in Inches		
		A	B	C
FS141	1/2	1.50	0.93	0.73
FS142	3/4	1.87	1.14	0.95
FS143	1	2.00	1.41	1.19
FS144	1-1/4	2.50	1.83	1.53
FS145	1-1/2	2.87	2.06	1.77
FS146	2	3.44	2.53	2.23
FS147	2-1/2	4.00	3.30	2.90
FS148	3	4.49	3.94	3.54
FS149	3-1/2	4.92	4.45	4.05
FS150	4	5.23	4.96	4.55

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Features

- Assembled with tri-combo head screw
- 1/2" to 1" trade sizes have two screws
- 1-1/4" to 4" trade sizes have four screws

Applications

- For use in dry locations to couple two ends of EMT conduit
- OEC 1/2" to 4" couplings provide secure concrete-tight connections when taped
- Suitable for applications above 600V

Standard Material

- Steel

Standard Finish

- Zinc-electroplated

Certification

- 1/2"-2" cULus Listed (E539274)
- 2-1/2"-4" cULus Listed (E539275)
- NEMA FB1

