

Watertight Conduit Hubs

Catalog ID	Trade Size	Dimensions In Inches		
		A	B	C
FWTH050	1/2	1.43	1.50	0.55
FWTH075	3/4	1.68	1.50	0.74
FWTH100	1	2.00	1.80	0.94
FWTH125	1-1/4	2.37	1.80	1.28
FWTH150	1-1/2	2.75	1.90	1.51
FWTH200	2	3.25	1.90	1.97

Features

- Used to connect threaded RIGID/IMC conduit to an enclosure or load center requiring a water-tight joint at knockouts or slip-fit holes.
- Meets NEMA Sealing Requirements

Applications


- Flame retardant, insulated throat prevents cable stripping.
- Includes "O-Ring" providing an oil, dust, and rain-tight seal.
- Includes over-sized Zinc Die Cast locknut providing a vibration free application and positive grounding.

Certification

- CULus Listed

Standard Material
• Zinc die-cast

Standard Finish
• Zinc-electroplated



Insulated Watertight Conduit Hubs

Catalog ID	Trade Size	Dimensions In Inches		
		A	B	C
FIWTH050	1/2	1.43	1.50	0.55
FIWTH075	3/4	1.68	1.50	0.74
FIWTH100	1	2.00	1.80	0.94
FIWTH125	1-1/4	2.37	1.80	1.28
FIWTH150	1-1/2	2.75	1.90	1.51
FIWTH200	2	3.25	1.90	1.97

Features

- Used to connect threaded RIGID/IMC conduit to an enclosure or load center requiring a water-tight joint at knockouts or slip-fit holes.
- Meets NEMA Sealing Requirements

Applications

- Flame retardant, insulated throat prevents cable stripping.
- Includes insulated throat liner.
- Includes "O-Ring" providing an oil, dust, and rain-tight seal.
- Includes over-sized Zinc Die Cast locknut providing a vibration free application and positive grounding.

Certification

- CULus Listed

Standard Material
• Zinc die-cast

Standard Finish
• Zinc-electroplated

