

60 Amp Non Fused AC Disconnect Pull Out

Features

- Used to disconnect power from an air conditioning unit
- Features a metallic enclosure for outdoor use
- Puller type with no fuse
- Compatible with copper or aluminum lug wire range 14-3

Applications

- 60 Amp 240-Volt Non-Fuse Metallic AC Disconnect is designed to stop the power going to an air conditioning unit to allow for safe working conditions.
- puller type and is UL listed with an enclosed pull-out switch.

Standard Material

- Galvanized steel

Standard Finish

- Powder Coated

Power Rating


- Rating : 10 HP

Certification

- CULus Listed (E534837)

Electrical Rating

- Voltage : 240 V - 1 Phase
- Current : 60 Amp



Catalog ID	CU/AL for Load/Line	CU/AL for Ground	A	B	C
OEC5802	14-2 AWG	14-2 AWG	5.00	2.50	7.50

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

60 Amp Non Fused AC Disconnect Non-Automatic Switch

Features

- Non-fusible switch style disconnect
- NEMA type 3R enclosure and for outdoor use
- 240VAC
- Lug wire range AWG Cu/Al 14-3

Applications

- 60 Amp AC Disconnect is used to cut off the power when servicing an Air conditioning unit. Non-Automatic Disconnect.

Standard Material

- Galvanized steel

Standard Finish

- Powder Coated

Power Rating


- Rating : 10 HP

Certification

- CULus Listed (E534837)

Electrical Rating

- Voltage : 240 V - 1 Phase
- Current : 60 Amp



Catalog ID	CU/AL for Load/Line	CU/AL for Ground	A	B	C
OEC5812	14-2 AWG	14-2 AWG	5.00	2.50	7.50

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

30 Amp Fused AC Disconnect Switch

Features

- Use to disconnect power from an air-conditioning unit
- NEMA 3R-rated steel enclosure for outdoor use
- Single phase
- Lug wire range is AWG #14 - 3 copper/aluminum

Applications

- 30 Amp 120/240-Volt 240-Watt Fused (requires 2 fuses installed on the back side of the puller).
- AC Disconnect has a NEMA 3R-rated

Standard Material

- Galvanized steel

Standard Finish

- Powder Coated

Power Rating


- Rating : 3 HP

Certification

- CULus Listed (E534837)

Electrical Rating

- Voltage : 240 V - 1 Phase
- Current : 30 Amp



Catalog ID	CU/AL for Load/Line	CU/AL for Ground	A	B	C
OEC5832	14-3 AWG	14-3 AWG	5.20	2.85	6.00

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

60 Amp Fused AC Disconnect Switch

Features

- Use to disconnect power from an air conditioning unit
- NEMA type 3R enclosure and for outdoor use
- Compatible with lug wire range 14-3

Applications

- 60 Amp 240-Volt Fused (requires 2 fuses installed on the back side of the puller).

Standard Material

- Galvanized steel

Standard Finish

- Powder Coated

Power Rating


- Rating : 10 HP

Certification

- CULus Listed (E534837)

Electrical Rating

- Voltage : 240 V - 1 Phase
- Current : 60 Amp



Catalog ID	CU/AL for Load/Line	CU/AL for Ground	A	B	C
OEC5862	14-3 AWG	14-3 AWG	5.20	3.10	9.25

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)